

MÜNCHEN LED m1200

6320lm, PMMA Transopal® (impact strengthened), 840/4000K, medium beam

Article No: 455 480 34 24 - MC9

LED

EL

IP 65

CE

RoHS

REACH

RoHS


RoHS

IK 07

PMMA



illustration may differ



medium beam

DIMENSIONS

| L | B | H | a | b | max. weight |
|---------|--------|-------|---------|---|-------------|
| 1392 mm | 191 mm | 80 mm | 1103 mm | - | 5.6 kg |

DESCRIPTION

Ceiling and recessed polymer luminaire with LED lamps. Flat and weather-proof polymer luminaire housing. Thermally separated lamp chamber and transformer chamber. Short sealing system consisting of age resistant, form retaining silicone/synthetic rubber. Lamp diffuser with internal aluminium reflector (MIRO-SILVER®). Built-in transformer. Ready for connection with two access covers (360 mm), four M20 cable entries on face side and through wiring. Mounting with split washers for easy assembly. Captive end caps.

created on: 2018-11-20 (ext.) Subject to technical changes without prior notice

MÜNCHEN LED m1200

6320lm, PMMA Transopal® (impact strengthened), 840/4000K, medium beam

Article No: 455 480 34 24 - MC9

CHARACTERISTICS

| | | | |
|-------------------------|---------------------------------------|--------------------|--------------------------------------------------------------------------------------------------------|
| Version | m1200 | Lamp power | 1 x 41 W |
| Lamp | LED | System power | 44 W |
| Lamp service life | L80 B10 > 60.000 h at +40°C | Colour temperature | White, 840/4000 K, Ra > 80 |
| Extreme-temperature | -25°C to +40°C | Luminous flux lamp | 6320 lm |
| Number of lamps | 1-lamp | Protection class | II |
| Cover material | Plastic | IP-rating | IP65 |
| Colour housing | White | Type of gear | LED operating device current-controlled, Not dimmable, 220 V - 240 V AC/DC |
| Cover | PMMA Transopal® (impact strengthened) | Through-wiring | 4 x 1,5 mm ² |
| Light distribution | medium beam | Impact strength | IK07 |
| Manufacturer warranty | 5 years | Installation type | recessed mounted, Surface mounting, recessed mounting, ceiling mounting, single mounting, row mounting |
| ENEC / VDE | YESYES | | |
| EL (Emergency Lighting) | optional | | |

DIAGRAMS

