


PRODUCT DETAILS



Dimensions



Accessories



NOVEL L ASYM

NOVEL L ASYM MATT REF IP40 LED
2550lm/830 1x29W, FIX, RAL 9003

DOWNLOADS

[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)

Description


MOUNTING	Ceiling recessed
LIGHT SOURCE	LED
OPTICAL SYSTEM	Asymmetric matt reflector (ASM)
LIGHT DISTRIBUTION	Asymmetric
WIRING	Electronic control gear FIX (ECG)
MATERIALS	Diffuser: microprismatic PMMA Housing: sheet steel Reflector: matt anodised aluminium Trim: sheet steel
SURFACE FINISH	Trim: white RAL 9003 (W03)
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	2550 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	29 W
SYSTEM EFFICACY	88 lm/W
CORRELATED COLOUR TEMPERATURE	3000 K
COLOUR RENDERING INDEX	80 Ra
COLOUR TOLERANCE	3 SDCM
EEC	A++ / A+ / A
PROTECTION CLASS	II
THERMAL MANAGEMENT	Passive
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L80 / B10
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C
IP PROTECTION DEGREE	IP20, optical part IP40
DIMENSIONS (L x W x H)	265 x 265 x 130 mm
OPENING (L x W)	250 x 250 mm
WEIGHT	1,5 kg

AREAS OF APPLICATION ARCHITECTURE AND MEDIA

RETAIL AND PRESENTATION



LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.