



PRODUCT DETAILS



Dimensions



Accessories



NOVEL M

NOVEL M POLISHED REF IP40 LED
2650lm/840 1x24W, FIX, RAL 9003

DOWNLOADS

[Certificates](#)
[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)


Description

MOUNTING	Ceiling recessed
LIGHT SOURCE	LED
OPTICAL SYSTEM	Polished reflector (PRE)
BEAM ANGLE	80°
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX (ECG)
MATERIALS	Diffuser: diamond microprismatic PMMA Housing: sheet steel Reflector: polished anodised aluminium Trim: sheet steel
SURFACE FINISH	Trim: white RAL 9003 (W03)
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	2650 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	24 W
SYSTEM EFFICACY	110 lm/W
COLOUR RENDERING INDEX	80 Ra
COLOUR TOLERANCE	3 SDCM
EEC	A++ / A+ / A
PROTECTION CLASS	II
THERMAL MANAGEMENT	Passive
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L80 / B10
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C
IP PROTECTION DEGREE	IP20, optical part IP40
DIMENSIONS (L x W x H)	215 x 215 x 107 mm
OPENING (L x W)	200 x 200 mm
WEIGHT	1,1 kg

AREAS OF APPLICATION

[EDUCATION](#)
[HOSPITALITY](#)
[HOUSE AND FLAT](#)

LIDC



HEALTH AND CARE

RETAIL AND PRESENTATION

OFFICE



ECO FRIENDLY



ENERGY SAVING



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.