




PRODUCT DETAILS



Dimensions



Accessories



FREYN II

FREYN II PV4 LED 4250lm/840 1x31W, FIX, RAL 9003

DOWNLOADS

[Datasheet](#)

[Product sheet](#)

[Installation manual](#)

[IES file](#)

[LDT file](#)

[EEC](#)

Description

MOUNTING

Ceiling recessed

PVx - T-ceiling

LIGHT SOURCE

LED

OPTICAL SYSTEM

Microprismatic diffuser (MCD)

LIGHT DISTRIBUTION

Direct

WIRING

Electronic control gear FIX (ECG)

MATERIALS

Housing: sheet steel

SURFACE FINISH

Housing: white RAL 9003 (W03)

ACCESSORIES

Frame for plasterboard installation

VOLTAGE

220-240 V, 50-60 Hz

POWER FACTOR

> 0,95

NET LUMEN OUTPUT (Ta=25°C)

4250 lm

LUMINOUS FLUX TOLERANCE

+/- 10 %

POWER CONSUMPTION

31 W

SYSTEM EFFICACY

137 lm/W

CORRELATED COLOUR TEMPERATURE

4000 K

COLOUR RENDERING INDEX

80 Ra

COLOUR TOLERANCE

3 SDCM

EEC

A++ / A+ / A

PROTECTION CLASS

I

THERMAL MANAGEMENT

Passive

AMBIENT OPERATING TEMPERATURE

From -20 °C to +35 °C

IP PROTECTION DEGREE

IP20, optical part IP40

DIMENSIONS (L x W x H)

PV4: 1195 x 295 x 51 mm

WEIGHT

3 kg

AREAS OF APPLICATION

EDUCATION


HEALTH AND CARE

OFFICE





LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.