



PRODUCT DETAILS



Dimensions



Accessories



PRETTUS L

PRETTUS L POLISHED REF IP40 LED
2900lm/830 1x29W, FIX, RAL 9003

DOWNLOADS

[Certificates](#)
[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)

Description


MOUNTING	Ceiling recessed
LIGHT SOURCE	LED
OPTICAL SYSTEM	Polished reflector (PRE)
BEAM ANGLE	69°
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX (ECG)
MATERIALS	Diffuser: microprismatic PMMA Housing: sheet steel Reflector: polished anodised aluminium Trim: die cast aluminium Trim: white RAL 9003 (W03)
SURFACE FINISH	
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	2900 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	29 W
SYSTEM EFFICACY	100 lm/W
CORRELATED COLOUR TEMPERATURE	3000 K
COLOUR RENDERING INDEX	80 Ra
COLOUR TOLERANCE	3 SDCM
EEC	A++ / A+ / A
PROTECTION CLASS	II
THERMAL MANAGEMENT	Passive
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L80 / B10
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C
IP PROTECTION DEGREE	IP20, optical part IP40
DIMENSIONS	Diameter - 266 mm, height - 140 mm
OPENING	Diameter - 254 mm
WEIGHT	1,3 kg

AREAS OF APPLICATION EDUCATION

HOSPITALITY

HOUSE AND FLAT

LIDC



HEALTH AND CARE

RETAIL AND PRESENTATION

OFFICE



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.