

# PRODUCT DATASHEET

## VALUE CEILING 23 W 3000 K

LED VALUE CEILING | Wall and ceiling luminaires



---

### AREAS OF APPLICATION

- Corridors
- Entrances / Hallways

---

### PRODUCT BENEFITS

- Direct connection to AC power supply thanks to integrated control gear
- Long lifetime thanks to LED technology
- Mercury-free technology
- Uniform room illumination

---

### PRODUCT FEATURES

- Beam angle: 120°
- Color rendering index  $R_a : \geq 80$
- Available with color temperature: 3,000 K, 4,000 K, 6,500 K



---

**TECHNICAL DATA****Electrical data**

|                 |         |
|-----------------|---------|
| Nominal wattage | 23.00 W |
| Nominal voltage | 220 V   |
| Mains frequency | 5060 Hz |

**Photometrical data**

|                           |            |
|---------------------------|------------|
| Color temperature         | 3000 K     |
| Color rendering index Ra  | ≥80        |
| Light color (designation) | Warm White |
| Luminous flux             | 1750 lm    |
| Luminous efficacy         | 76 lm/W    |

**Dimensions & weight**

|                |          |
|----------------|----------|
| Diameter       | 350.0 mm |
| Height         | 85.0 mm  |
| Product weight | 470.00 g |

**Colors & materials**

|                |                    |
|----------------|--------------------|
| Body material  | Metal              |
| Housing color  | White              |
| Product color  | White              |
| Cover material | Polycarbonate (PC) |

**Lifespan**

|                            |        |
|----------------------------|--------|
| Number of switching cycles | 100000 |
|----------------------------|--------|

**Additional product data**

|                   |         |
|-------------------|---------|
| Mounting type     | Surface |
| Mounting location | Ceiling |

**Capabilities**

|                    |          |
|--------------------|----------|
| Dimmable           | No       |
| Type of connection | Terminal |

**Certificates & standards**

|                    |      |
|--------------------|------|
| Protection class   | II   |
| Type of protection | IP20 |

---

**LOGISTICAL DATA**

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075802308 | Folding carton box<br>1      | 377 mm x 107 mm x 380 mm             | 777.00 g     | 15.33 dm <sup>3</sup> |
| 4058075074156 | Shipping carton box<br>5     | 388 mm x 383 mm x 381 mm             | 4091.00 g    | 56.62 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.