

PRODUCT FAMILY DATASHEET

LED VALUE CEILING

Wall and ceiling luminaires



AREAS OF APPLICATION

- Corridors
- Entrances / Hallways

PRODUCT BENEFITS

- Direct connection to AC power supply thanks to integrated control gear
- Long lifetime thanks to LED technology
- Mercury-free technology
- Uniform room illumination

PRODUCT FEATURES

- Beam angle: 120°
- Color rendering index $R_a : \geq 80$
- Available with color temperature: 3,000 K, 4,000 K, 6,500 K



TECHNICAL DATA

Product description	Electrical data				Photometrical data		Dimensions & weight				Colors & materials
	Nominal wattage	Nominal voltage	Mains frequency	Power factor λ	Color temperature	Luminous flux	Diameter	Height	Product weight	Length	Body material
VALUE CEILING 10 W 3000 K	10.00 W	220 V	50/60 Hz	0.5	3000 K	700 lm	250.0 mm	85.0 mm	320.00 g		Metal
VALUE CEILING 10 W 4000 K	10.00 W	220 V	50/60 Hz		4000 K	800 lm	250.0 mm	85.0 mm	320.00 g		Metal
VALUE CEILING 10 W 6500 K	10.00 W	220 V	50/60 Hz		6500 K	800 lm	250.0 mm	85.0 mm	320.00 g		Metal
VALUE CEILING 10 W 3000 K 100...240 V	10.00 W	100...240 V	50/60 Hz	0.5	3000 K	760 lm	250.0 mm	63.0 mm	320.00 g	85.0 mm	Metal
VALUE CEILING 10 W 4000 K 100...240 V	10.00 W	100...240 V	50/60 Hz	0.5	4000 K		250.0 mm	63.0 mm	320.00 g	85.0 mm	Metal
VALUE CEILING 10 W 6500 K 100...240 V	10.00 W	100...240 V	50/60 Hz	0.5	6500 K		250.0 mm	63.0 mm	320.00 g	85.0 mm	Metal
VALUE CEILING 20 W 3000 K	20.00 W	220 V	50/60 Hz		3000 K	1500 lm	350.0 mm	65.0 mm	470.00 g	85.0 mm	Metal
VALUE CEILING 20 W 4000 K	20.00 W	220 V	50/60 Hz		4000 K	1600 lm	350.0 mm	85.0 mm	470.00 g	85.0 mm	Metal
VALUE CEILING 20 W 6500 K	20.00 W	220 V	50/60 Hz		6500 K	1600 lm	350.0 mm	65.0 mm	470.00 g	85.0 mm	Metal
VALUE CEILING 23 W 3000 K	23.00 W	220 V	50/60 Hz		3000 K	1750 lm	350.0 mm	85.0 mm	470.00 g		Metal
VALUE CEILING 23 W 4000 K	23.00 W	220 V	50/60 Hz		4000 K	1850 lm	350.0 mm	85.0 mm	470.00 g		Metal
VALUE CEILING 23 W 6500 K	23.00 W	220 V	50/60 Hz		6500 K	1850 lm	350.0 mm	85.0 mm	470.00 g		Metal
VALUE CEILING 42 W 3000 K	42.00 W	220...240 V	50/60 Hz		3000 K	3500 lm	500.0 mm	85.0 mm	960.00 g		Metal
VALUE CEILING 42 W 4000 K	42.00 W	220...240 V	50/60 Hz		4000 K	3700 lm	500.0 mm	85.0 mm	960.00 g		Metal
VALUE CEILING 42 W 6500 K	42.00 W	220...240 V	50/60 Hz		6500 K	3700 lm	500.0 mm	100.0 mm	960.00 g		Metal
VALUE CEILING 42 W 3000 K 100...240 V	42.00 W	220...240 V	50/60 Hz	0.90	3000 K		500.0 mm	100.0 mm	1230.00 g		Metal
VALUE CEILING 23 W 3000 K 100...240 V	23.00 W	100...240 V	50/60 Hz	0.5	3000 K	1770 lm	330.0 mm	63.0 mm	470.00 g		Metal
VALUE CEILING 23 W 4000 K 100...240 V	23.00 W	100...240 V	50/60 Hz	0.5	4000 K	1860 lm	330.0 mm	63.0 mm	470.00 g		Metal
VALUE CEILING 23 W 6500 K 100...240 V	23.00 W	100...240 V	50/60 Hz	0.5	6500 K	1860 lm	330.0 mm	63.0 mm	470.00 g		Metal
VALUE CEILING 42 W 6500 K 100...240 V	42.00 W	220...240 V	50/60 Hz	0.90	6500 K		500.0 mm	100.0 mm	1230.00 g		Metal
VALUE CEILING 42 W 4000 K 100...240 V	42.00 W	220...240 V	50/60 Hz	0.90	4000 K		500.0 mm	100.0 mm	1230.00 g		Metal

Product description	Product color	Cover material	Lifespan		Capabilities		Certificates & standards	
			Number of switching cycles	Lifespan	Dimmable	Type of connection	Protection class	Type of protection
VALUE CEILING 10 W 3000 K	White	Polycarbonate (PC)	30000		No	Terminal	II	IP20
VALUE CEILING 10 W 4000 K	White	Polycarbonate (PC)	100000		No	Terminal	II	IP20
VALUE CEILING 10 W 6500 K	White	Polycarbonate (PC)	100000		No	Terminal	II	IP20
VALUE CEILING 10 W 3000 K 100...240 V	White	Polycarbonate (PC)	30000	15000 h	No	Terminal		
VALUE CEILING 10 W 4000 K 100...240 V	White	Polycarbonate (PC)	30000	15000 h	No	Terminal		
VALUE CEILING 10 W 6500 K 100...240 V	White	Polycarbonate (PC)	30000	15000 h	No	Terminal		
VALUE CEILING 20 W 3000 K	White	Polycarbonate (PC)			No	Terminal	II	IP20
VALUE CEILING 20 W 4000 K	White	Polycarbonate (PC)			No	Terminal	II	IP20
VALUE CEILING 20 W 6500 K	White	Polycarbonate (PC)			No	Terminal	II	IP20
VALUE CEILING 23 W 3000 K	White	Polycarbonate (PC)	100000		No	Terminal	II	IP20
VALUE CEILING 23 W 4000 K	White	Polycarbonate (PC)	100000		No	Terminal	II	IP20
VALUE CEILING 23 W 6500 K	White	Polycarbonate (PC)	100000		No	Terminal	I	IP20
VALUE CEILING 42 W 3000 K	White	Polycarbonate (PC)			No	Terminal	II	IP20
VALUE CEILING 42 W 4000 K	White	Polycarbonate (PC)			No	Terminal	II	IP20
VALUE CEILING 42 W 6500 K	White	Polycarbonate (PC)			No	Terminal	II	IP20
VALUE CEILING 42 W 3000 K 100...240 V	White	Polycarbonate (PC)	30000	15000 h	No	Terminal	II	IP20
VALUE CEILING 23 W 3000 K 100...240 V	White	Polycarbonate (PC)	30000	15000 h	No	Terminal	I	IP20
VALUE CEILING 23 W 4000 K 100...240 V	White	Polycarbonate (PC)	30000	15000 h	No	Terminal	I	IP20
VALUE CEILING 23 W 6500 K 100...240 V	White	Polycarbonate (PC)	30000	15000 h	No	Terminal	I	IP20
VALUE CEILING 42 W 6500 K 100...240 V	White	Polycarbonate (PC)	30000	15000 h	No	Terminal	II	IP20
VALUE CEILING 42 W 4000 K 100...240 V	White	Polycarbonate (PC)	30000	15000 h	No	Terminal	II	IP20

APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075074064	Shipping carton box 5	383 mm x 303 mm x 311 mm	2698.00 g	36.09 dm ³
4058075074071	Shipping carton box 5	383 mm x 303 mm x 311 mm	2698.00 g	36.09 dm ³
4058075074088	Shipping carton box 5	383 mm x 303 mm x 311 mm	2698.00 g	36.09 dm ³
4058075073975	Shipping carton box 5	383 mm x 303 mm x 311 mm	2698.00 g	36.09 dm ³
4058075073982	Shipping carton box 5	383 mm x 303 mm x 311 mm	2698.00 g	36.09 dm ³
4058075073999	Shipping carton box 5	383 mm x 303 mm x 311 mm	2698.00 g	36.09 dm ³
4058075074101	Shipping carton box 5	388 mm x 383 mm x 381 mm	4091.00 g	56.62 dm ³
4058075802377	Shipping carton box 5	558 mm x 393 mm x 405 mm	5227.00 g	88.81 dm ³
4058075074118	Shipping carton box 5	388 mm x 383 mm x 381 mm	4091.00 g	56.62 dm ³
4058075802391	Shipping carton box 5	558 mm x 393 mm x 405 mm	5227.00 g	88.81 dm ³
4058075074132	Shipping carton box 5	388 mm x 383 mm x 381 mm	4091.00 g	56.62 dm ³
4058075802414	Shipping carton box 5	558 mm x 393 mm x 405 mm	5227.00 g	88.81 dm ³
4058075074156	Shipping carton box 5	388 mm x 383 mm x 381 mm	4091.00 g	56.62 dm ³
4058075074170	Shipping carton box 5	388 mm x 383 mm x 381 mm	4091.00 g	56.62 dm ³

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075074194	Shipping carton box 5	388 mm x 383 mm x 381 mm	4091.00 g	56.62 dm ³
4058075074286	Shipping carton box 5	558 mm x 483 mm x 566 mm	7584.00 g	152.54 dm ³
4058075074309	Shipping carton box 5	558 mm x 483 mm x 566 mm	7584.00 g	152.54 dm ³
4058075074323	Shipping carton box 5	558 mm x 483 mm x 566 mm	7584.00 g	152.54 dm ³
4058075074095	Shipping carton box 5	558 mm x 483 mm x 566 mm	7584.00 g	152.54 dm ³
4058075074019	Shipping carton box 5	388 mm x 383 mm x 381 mm	4091.00 g	56.62 dm ³
4058075074033	Shipping carton box 5	388 mm x 383 mm x 381 mm	4091.00 g	56.62 dm ³
4058075074057	Shipping carton box 5	388 mm x 383 mm x 381 mm	4091.00 g	56.62 dm ³
4058075074149	Shipping carton box 5	558 mm x 483 mm x 566 mm	7584.00 g	152.54 dm ³
4058075074125	Shipping carton box 5	558 mm x 483 mm x 566 mm	7584.00 g	152.54 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.