

PRODUCT DATASHEET

VALUE CEILING 20 W 3000 K

LED VALUE CEILING | Wall and ceiling luminaires



AREAS OF APPLICATION

- Corridors
- Entrances / Hallways

PRODUCT BENEFITS

- Direct connection to AC power supply thanks to integrated control gear
- Long lifetime thanks to LED technology
- Mercury-free technology
- Uniform room illumination

PRODUCT FEATURES

- Beam angle: 120°
- Color rendering index $R_a : \geq 80$
- Available with color temperature: 3,000 K, 4,000 K, 6,500 K



TECHNICAL DATA**Electrical data**

Nominal wattage	20.00 W
Nominal voltage	220 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	3000 K
Color rendering index Ra	≥80
Light color (designation)	Warm White
Luminous flux	1500 lm
Luminous efficacy	75 lm/W

Dimensions & weight

Length	85.0 mm
Diameter	350.0 mm
Height	65.0 mm
Product weight	470.00 g

Colors & materials

Body material	Metal
Housing color	White
Product color	White
Cover material	Polycarbonate (PC)

Additional product data

Mounting type	Surface
Mounting location	Ceiling

Capabilities

Dimmable	No
Type of connection	Terminal

Certificates & standards

Protection class	II
Type of protection	IP20

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075802360	Folding carton box 1	377 mm x 107 mm x 380 mm	777.00 g	15.33 dm ³
4058075074101	Shipping carton box 5	388 mm x 383 mm x 381 mm	4091.00 g	56.62 dm ³
4058075802377	Shipping carton box 5	558 mm x 393 mm x 405 mm	5227.00 g	88.81 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.