

# PRODUCT DATASHEET

## VALUE CEILING 24 W 3000 K 4000 5000

LED VALUE Tri-Colour Oyster Light | LED ceiling luminaires with three settable color temperatures



---

### AREAS OF APPLICATION

- Living areas (living rooms, dining rooms, bedrooms etc.)

---

### PRODUCT BENEFITS

- Easy and quick installation
- Slim and sleek design

---

### PRODUCT FEATURES

- Three light colors selectable via slide switch
- Lifetime (L70/B50): up to 30,000 h
- Beam angle: 120°
- Type of protection: IP20



---

**TECHNICAL DATA****Electrical data**

Nominal wattage	24.00 W
Operating mode	Integrated LED driver
Nominal voltage	220...240 V
Mains frequency	50/60 Hz

**Photometrical data**

Color temperature	3000/4000/5000 K
Color rendering index Ra	≥80
Light color (designation)	Warm White/Cool White/Daylight
Luminous flux	1920/2160 lm
Luminous efficacy	80/90 lm/W

**Dimensions & weight**

Diameter	400.0 mm
Height	120.0 mm
Product weight	680.00 g

**Colors & materials**

Body material	Steel
Housing color	White
Product color	White
Cover material	Polymethylmethacrylate (PMMA)

**Temperatures & operating conditions**

Ambient temperature range	-20...40 °C
---------------------------	-------------

**Additional product data**

Mounting type	Surface
Mounting location	Ceiling

**Capabilities**

Dimmable	No
----------	----

**Certificates & standards**

Protection class	I
Type of protection	IP20

---

**LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075207561	Folding carton box 1	415 mm x 130 mm x 415 mm	867.00 g	22.39 dm <sup>3</sup>
4058075207578	Shipping carton box 5	675 mm x 430 mm x 440 mm	6074.00 g	127.71 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.