




# p.mini & p.mirror

Aufbauleuchte | Surface-mount luminaire | Luminaires en saillie | Apparecchio a plafone



**A++** **A**

230V IP20 IP44  $R_a > 80$  up to L90/50.000h MacAdam 3 DALI switchDIM



## LED

3000K, 4000K  
 up to 113 lm/W, up to 2011 lm/m  
 $R_a > 80$ , MacAdam 3  
 non-dim/DALI  
 IEC 62471: Blue light hazard: RG  $\leq 1$   
 Lifetime up to L80/50.000h

## Optic

direct  
 satiné U

## Options

RAL of your choice (p. 449)

## Housing

powder coated, anodised

A6C0

RAL 9016

RAL 9005



1 Länge | Length | Longueur | Lunghezza

p.mini IP20		p.mirror IP44	
580 mm	058	600 mm	060
860 mm	086	900 mm	090
1140 mm	114	1200 mm	120
1420 mm	142	1500 mm	150

2 Gehäusefarbe | Housing colour | Couleur du luminaire | Colore profilo

aluminium anodised	A6C0
weiß   white   blanc   bianco (RAL 9016)	9016
schwarz   black   noir   nero (RAL 9005)	9005

RAL colours on request (p. 449)

3 Schutzart | Protection rating | Indice de protection | Grado di protezione

IP20 p.mini	C
IP44 p.mirror	P

4 Farbtemperatur | Colour temperature | Température de couleur | Temperatura colore

3000 K	830
4000 K	840

5 Output

low output non-dim	L1
low output DALI	L3

Beispiel | Example | Exemple | Esempio

p.mirror 600 mm, white, IP44, 4000 K, low output DALI, satiné

**P67A060-9016P1840L3U**

Luminous Flux (lm)	3000 K	4000 K
580 / 600 mm	882 lm	928 lm
860 / 900 mm	1604 lm	1688 lm
1140 / 1200 mm	2139 lm	2252 lm
1420 / 1500 mm	2673 lm	2813 lm

System Power (W)	
580 / 600 mm	12 W
860 / 900 mm	16 W
1140 / 1200 mm	21 W
1420 / 1500 mm	25 W

Weight (kg)	
580 / 600 mm	1,2 kg
860 / 900 mm	1,6 kg
1140 / 1200 mm	2,2 kg
1420 / 1500 mm	2,5 kg

