

PHALANX 430 430



2490lm, PC (fracture proof) opal white, 840/4000K, medium beam

Article No: 318 480 34 02

LED



illustration may differ



XARA® (optional)

medium beam

DIMENSIONS

L	B	H	a	b	max. weight
430 mm	430 mm	120 mm	258 mm	-	5.8 kg

DESCRIPTION

Extremely impact-resistant, vandalism-proof luminaire with LED lamps. Vandalism-proof up to 150 joules / IK 10+. Luminaire housing made of metal, powder-coated. Short sealing system consisting of age resistant, form retaining silicone/synthetic rubber. Curved, 4 mm thick luminaire cover, opalwhite. Built-in transformer. Ready for connection with two cable entries M20 at the rear. Mounting with four concealed mounting apertures at the rear.

created on: 2018-11-23 (ext.) Subject to technical changes without prior notice

PHALANX 430 430

2490lm, PC (fracture proof) opal white, 840/4000K, medium beam

Article No: 318 480 34 02

CHARACTERISTICS

Version	430
Lamp	LED
Lamp service life	L80 B10 > 100.000 h at +30°C
Extreme-temperature	-25°C to +30°C
Number of lamps	1-lamp
Cover material	steel
Colour housing	Anthracite, similar to RAL 7016
Silicone reduced	YES
Cover	PC (fracture proof) opal white
Light distribution	medium beam
Manufacturer warranty	8 years
EL (Emergency Lighting)	optional

Lamp power	1 x 11 W
System power	17 W
Colour temperature	White, 840/4000 K, Ra > 80
Luminous flux lamp	2490 lm
Protection class	II
IP-rating	IP65
Type of gear	LED operating device current-controlled, other, Not dimmable, 220 V - 240 V AC/DC, 50-60 Hz
Through-wiring	without
Impact strength	> IK10
Installation type	Surface mounting, ceiling mounting, wall mounting
Halogen-free	YES
Transient protection	2 kV

DIAGRAMS

