

PHALANX 620 620



5450lm, PC (fracture proof) opal white, 840/4000K, medium beam

Article No: 319 680 34 02

LED



illustration may differ



XARA® (optional)

medium beam

DIMENSIONS

L	B	H	a	b	max. weight
620 mm	620 mm	128 mm	3750 mm	-	11.5 kg

DESCRIPTION

Extremely impact-resistant, vandalism-proof luminaire with LED lamps. Vandalism-proof up to 150 joules / IK 10+. Luminaire housing made of metal, powder-coated. Short sealing system consisting of age resistant, form retaining silicone/synthetic rubber. Curved, 4 mm thick luminaire cover, opalwhite. Built-in transformer. Ready for connection with two cable entries M20 at the rear. Mounting with four concealed mounting apertures at the rear.

created on: 2018-11-23 (ext.) Subject to technical changes without prior notice

PHALANX 620 620

5450lm, PC (fracture proof) opal white, 840/4000K, medium beam

Article No: 319 680 34 02

CHARACTERISTICS

Version	620	Lamp power	1 x 51 W
Lamp	LED	System power	54 W
Lamp service life	L80 B10 > 100.000 h at +40°C	Colour temperature	White, 840/4000 K, Ra > 80
Extreme-temperature	-40°C to +40°C	Luminous flux lamp	5450 lm
Number of lamps	1-lamp	Protection class	II
Cover material	steel	IP-rating	IP65
Colour housing	Anthracite, similar to RAL 7016	Type of gear	LED operating device current-controlled, other, Not dimmable, 220 V - 240 V AC/DC, 50-60 Hz
Silicone reduced	YES	Through-wiring	without
Cover	PC (fracture proof) opal white	Impact strength	> IK10
Light distribution	medium beam	Installation type	Surface mounting, ceiling mounting, wall mounting
Manufacturer warranty	8 years	Halogen-free	YES
ENEC / VDE	YESYES	Transient protection	2 kV
EL (Emergency Lighting)	optional		

DIAGRAMS

