




PRODUCT DETAILS



Dimensions



Accessories



PRETTUS L ASYM

PRETTUS L ASYM MATT + TRANSPARENT
LED 2250lm/840 1x29W, FIX, RAL 9003


DOWNLOADS

[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)

Description

MOUNTING	Ceiling recessed
LIGHT SOURCE	LED
OPTICAL SYSTEM	Asymmetric matt reflector + transparent cover (AMT)
LIGHT DISTRIBUTION	Asymmetric
WIRING	Electronic control gear FIX (ECG)
MATERIALS	Cover: transparent PMMA Diffuser: microprismatic PMMA Housing: sheet steel Reflector: matt anodised aluminium Trim: die cast aluminium
SURFACE FINISH	Trim: white RAL 9003 (W03)
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	2250 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	29 W
SYSTEM EFFICACY	78 lm/W
CORRELATED COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX	80 Ra
COLOUR TOLERANCE	3 SDCM
EEC	A++ / A+ / A
PROTECTION CLASS	II
THERMAL MANAGEMENT	Passive
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L80 / B10
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C
IP PROTECTION DEGREE	IP20, optical part IP54
WARNING	The luminaire is not suitable for use in outdoor applications
DIMENSIONS	Diameter - 266 mm, height - 140 mm
OPENING	Diameter - 254 mm
WEIGHT	1,3 kg

LIDC



AREAS OF APPLICATION

 ARCHITECTURE AND MEDIA

 RETAIL AND PRESENTATION



5 YEARS
WARRANTY



EEC
A++/A+/B



HEAT
SINK



MAINTENANCE
FREE



UV/IR



ECO
FRIENDLY



ENERGY
SAVING

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.