


## PRODUCT DETAILS



## Dimensions



## Accessories



# PRETTUS M ASYM

**PRETTUS M ASYM POLISHED +  
TRANSPARENT LED 2050lm/840 1x24W, FIX, RAL 9003**


## DOWNLOADS

[Datasheet](#)  
[Product sheet](#)  
[Installation manual](#)  
[IES file](#)  
[LDT file](#)  
[EEC](#)

## Description

<b>MOUNTING</b>	Ceiling recessed
<b>LIGHT SOURCE</b>	LED
<b>OPTICAL SYSTEM</b>	Aymmetric polished reflector + transparent cover (APT)
<b>LIGHT DISTRIBUTION</b>	Asymmetric
<b>WIRING</b>	Electronic control gear FIX (ECG)
<b>MATERIALS</b>	Diffuser: microprismatic PMMA Housing: sheet steel Reflector: polished anodised aluminium Trim: die cast aluminium
<b>SURFACE FINISH</b>	Trim: white RAL 9003 (W03)
<b>VOLTAGE</b>	220-240 V, 50-60 Hz
<b>POWER FACTOR</b>	> 0,95
<b>NET LUMEN OUTPUT (Ta=25°C)</b>	2050 lm
<b>LUMINOUS FLUX TOLERANCE</b>	+/- 10 %
<b>POWER CONSUMPTION</b>	24 W
<b>SYSTEM EFFICACY</b>	85 lm/W
<b>CORRELATED COLOUR TEMPERATURE</b>	4000 K
<b>COLOUR RENDERING INDEX</b>	80 Ra
<b>COLOUR TOLERANCE</b>	3 SDCM
<b>EEC</b>	A++ / A+ / A
<b>PROTECTION CLASS</b>	II
<b>THERMAL MANAGEMENT</b>	Passive
<b>SERVICE LIFETIME (Ta=25°C)</b>	50,000 hours / L80 / B10
<b>AMBIENT OPERATING TEMPERATURE</b>	From -20 °C to +35 °C
<b>IP PROTECTION DEGREE</b>	IP20, optical part IP54
<b>WARNING</b>	The luminaire is not suitable for use in outdoor applications
<b>DIMENSIONS</b>	Diameter - 216 mm, height - 119 mm
<b>OPENING</b>	Diameter - 204 mm
<b>WEIGHT</b>	1 kg

## LIDC



### AREAS OF APPLICATION

 ARCHITECTURE AND MEDIA

 RETAIL AND PRESENTATION



5 YEARS  
WARRANTY



EEC  
A++/A+/B



HEAT  
SINK



MAINTENANCE  
FREE



UV/IR



ECO  
FRIENDLY



ENERGY  
SAVING

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.