




PRODUCT DETAILS



Dimensions



Accessories



PRETTUS S SURFACED

**PRETTUS S SURFACED POLISHED +
TRANSPARENT LED 1350lm/840 1x15W, FIX, RAL 9003**

DOWNLOADS


[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)

Description

MOUNTING	Ceiling surfaced (SFD)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Polished reflector + transparent cover (PRT)
BEAM ANGLE	69°
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX (ECG)
MATERIALS	Diffuser: microprismatic PMMA Reflector: polished anodised aluminium Housing: extruded aluminium + sheet steel Housing: white RAL 9003 (W03)
SURFACE FINISH	
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	1350 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	15 W
SYSTEM EFFICACY	90 lm/W
CORRELATED COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX	80 Ra
COLOUR TOLERANCE	3 SDCM
EEC	A++ / A+ / A
PROTECTION CLASS	I
THERMAL MANAGEMENT	Passive
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C
IP PROTECTION DEGREE	IP20
DIMENSIONS	Diameter - 178 mm, height - 231 mm
WEIGHT	3,7 kg

AREAS OF APPLICATION [ARCHITECTURE AND MEDIA](#)
 [HOSPITALITY](#)
 [RETAIL AND PRESENTATION](#)

LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.