




PRODUCT DETAILS



Dimensions



Accessories



PRETTUS S SURFACED

**PRETTUS S SURFACED POLISHED +
TRANSPARENT LED 1650lm/830 1x19W, FIX, RAL 9003**

DOWNLOADS

[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)

Description


MOUNTING	Ceiling surfaced (SFD)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Polished reflector + transparent cover (PRT)
BEAM ANGLE	69°
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX (ECG)
MATERIALS	Diffuser: microprismatic PMMA Reflector: polished anodised aluminium Housing: extruded aluminium + sheet steel Housing: white RAL 9003 (W03)
SURFACE FINISH	
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	1650 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	19 W
SYSTEM EFFICACY	87 lm/W
CORRELATED COLOUR TEMPERATURE	3000 K
COLOUR RENDERING INDEX	80 Ra
COLOUR TOLERANCE	3 SDCM
EEC	A++ / A+ / A
PROTECTION CLASS	I
THERMAL MANAGEMENT	Passive
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L80 / B20
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C
IP PROTECTION DEGREE	IP20
DIMENSIONS	Diameter - 178 mm, height - 231 mm
WEIGHT	3,7 kg

AREAS OF APPLICATION ARCHITECTURE AND MEDIA

HOSPITALITY

RETAIL AND PRESENTATION

LIDC



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.