




PRODUCT DETAILS



UPCOMING NEW FAST RUNNER UPDATED PHASE-OUT PRODUCTS



DOWNLOADS

[Datasheet](#)

[Installation manual](#)

PRETTUS S SURFACED

Description Product map

MOUNTING	Ceiling surfaced (SFD)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Polished reflector + opal cover (PRO) Polished reflector + transparent cover (PRT)
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX / DALI (ECG / EDA)
MATERIALS	Cover: transparent / opal PMMA Diffuser: microprismatic PMMA Reflector: polished anodised aluminium Housing: extruded aluminium + sheet steel
SURFACE FINISH	Housing: white RAL 9003 (W03)
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L80 / B10 - 15 W 50,000 hours / L80 / B20 - 19 W
AMBIENT OPERATING TEMPERATURE	From -20 °C to +35 °C

AREAS OF APPLICATION ARCHITECTURE AND MEDIA

 HOSPITALITY

 RETAIL AND PRESENTATION



Accessories

List of products

PRODUCT NAME	STATUS	QUICK DOWNLOADS
PRETTUS S SURFACED POLISHED + TRANSPARENT LED 1250lm/830 1x15W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
PRETTUS S SURFACED POLISHED + TRANSPARENT LED 1350lm/840 1x15W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
PRETTUS S SURFACED POLISHED + TRANSPARENT LED 1650lm/830 1x19W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
PRETTUS S SURFACED POLISHED + TRANSPARENT LED 1750lm/840 1x19W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
PRETTUS S SURFACED POLISHED + OPAL LED 1300lm/840 1x15W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
PRETTUS S SURFACED POLISHED + OPAL LED 1200lm/830 1x15W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
PRETTUS S SURFACED POLISHED + OPAL LED 1700lm/840 1x19W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
PRETTUS S SURFACED POLISHED + OPAL LED 1600lm/830 1x19W, FIX, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
PRETTUS S SURFACED POLISHED + TRANSPARENT LED 1350lm/840 1x15W, DALI, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
PRETTUS S SURFACED POLISHED + TRANSPARENT LED 1250lm/830 1x15W, DALI, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
PRETTUS S SURFACED POLISHED + TRANSPARENT LED 1750lm/840 1x19W, DALI, RAL 9003		RFA / 3DS / IES / LDT / CURVE /
PRETTUS S SURFACED POLISHED + TRANSPARENT LED 1650lm/830 1x19W, DALI, RAL		RFA / 3DS / IES / LDT /

9003

[CURVE](#) /

PRETTUS S SURFACED POLISHED + OPAL LED 1300lm/840 1x15W, DALI, RAL 9003

[RFA](#) / [3DS](#) / [IES](#) / [LDT](#) /

[CURVE](#) /

PRETTUS S SURFACED POLISHED + OPAL LED 1200lm/830 1x15W, DALI, RAL 9003

[RFA](#) / [3DS](#) / [IES](#) / [LDT](#) /

[CURVE](#) /

PRETTUS S SURFACED POLISHED + OPAL LED 1600lm/830 1x19W, DALI, RAL 9003

[RFA](#) / [3DS](#) / [IES](#) / [LDT](#) /

[CURVE](#) /

PRETTUS S SURFACED POLISHED + OPAL LED 1700lm/840 1x19W, DALI, RAL 9003

[RFA](#) / [3DS](#) / [IES](#) / [LDT](#) /

[CURVE](#) /

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.