



## PRODUCT DETAILS



## Dimensions



## Accessories



# PRETTUS XTP

**PRETTUS XTP POLISHED + OPAL LED**  
**2100lm/840 1x24W, FIX, RAL 9003**

## DOWNLOADS

[Datasheet](#)  
[Product sheet](#)  
[Installation manual](#)  
[IES file](#)  
[LDT file](#)  
[EEC](#)

## Description


|                                      |   |
|--------------------------------------|---|
| <b>MOUNTING</b>                      | Ceiling recessed  |
| <b>LIGHT SOURCE</b>                  | LED   |
| <b>OPTICAL SYSTEM</b>                | Polished reflector + opal cover (PRO)   |
| <b>BEAM ANGLE</b>                    | 74°   |
| <b>LIGHT DISTRIBUTION</b>            | Direct  |
| <b>WIRING</b>                        | Electronic control gear FIX (ECG)   |
| <b>MATERIALS</b>                     | Diffuser: microprismatic PMMA<br>Housing: die-cast aluminium<br>Reflector: polished anodised aluminium<br>Cover: opal glass |
| <b>SURFACE FINISH</b>                | Trim: white RAL 9003 (W03)  |
| <b>VOLTAGE</b>                       | 220-240 V, 50-60 Hz   |
| <b>NET LUMEN OUTPUT (Ta=25°C)</b>    | 2100 lm   |
| <b>LUMINOUS FLUX TOLERANCE</b>       | +/- 10 %  |
| <b>POWER CONSUMPTION</b>             | 24 W  |
| <b>SYSTEM EFFICACY</b>               | 88 lm/W   |
| <b>CORRELATED COLOUR TEMPERATURE</b> | 4000 K  |
| <b>COLOUR RENDERING INDEX</b>        | 80 Ra   |
| <b>EEC</b>                           | A++ / A+ / A  |
| <b>PROTECTION CLASS</b>              | II  |
| <b>THERMAL MANAGEMENT</b>            | Passive   |
| <b>SERVICE LIFETIME (Ta=25°C)</b>    | 50,000 hours / L80 / B10  |
| <b>AMBIENT OPERATING TEMPERATURE</b> | From -25 °C to +35 °C   |
| <b>IP PROTECTION DEGREE</b>          | IP65  |
| <b>WARNING</b>                       | The luminaire is not suitable for use in outdoor applications   |
| <b>DIMENSIONS</b>                    | Diameter - 251 mm, height - 101 mm  |
| <b>OPENING</b>                       | Diameter - 232 mm   |
| <b>WEIGHT</b>                        | 2 kg  |

**AREAS OF APPLICATION** EDUCATION

HOSPITALITY

HOUSE AND FLAT

## LIDC



 INDUSTRY AND ENGINEERING

 HEALTH AND CARE

 RETAIL AND PRESENTATION



5 YEARS  
WARRANTY



EEC  
A++/A+/A



HEAT  
SINK



MAINTENANCE  
FREE



UV/IR



ECO  
FRIENDLY



ENERGY  
SAVING

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.