



PRODUCT DETAILS



Dimensions



Accessories



PRETTUS XTP

PRETTUS XTP POLISHED + TRANSPARENT
LED 2450lm/840 1x24W, FIX, RAL 9003

DOWNLOADS


[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)

Description

MOUNTING	Ceiling recessed
LIGHT SOURCE	LED
OPTICAL SYSTEM	Polished reflector + transparent cover (PRT)
BEAM ANGLE	72°
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX (ECG)
MATERIALS	Cover: transparent glass Diffuser: microprismatic PMMA Housing: die-cast aluminium Reflector: polished anodised aluminium Trim: die cast aluminium
	Trim: white RAL 9003 (W03)
SURFACE FINISH	
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	2450 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	24 W
SYSTEM EFFICACY	102 lm/W
CORRELATED COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX	80 Ra
COLOUR TOLERANCE	3 SDCM
EEC	A++ / A+ / A
PROTECTION CLASS	II
THERMAL MANAGEMENT	Passive
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L80 / B10
AMBIENT OPERATING TEMPERATURE	From -25 °C to +35 °C
IP PROTECTION DEGREE	IP65
WARNING	The luminaire is not suitable for use in outdoor applications
DIMENSIONS	Diameter - 251 mm, height - 101 mm
OPENING	Diameter - 232 mm
WEIGHT	2 kg

AREAS OF APPLICATION **EDUCATION**

LIDC



-  HOSPITALITY
-  HOUSE AND FLAT
-  INDUSTRY AND ENGINEERING
-  HEALTH AND CARE
-  RETAIL AND PRESENTATION



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.