



## PRODUCT DETAILS



## Dimensions



## Accessories



# PRETTUS XTP

**PRETTUS XTP POLISHED + TRANSPARENT**  
**LED 3350lm/840 1x30W, FIX, RAL 9003**

## DOWNLOADS


[Datasheet](#)  
[Product sheet](#)  
[Installation manual](#)  
[IES file](#)  
[LDT file](#)  
[EEC](#)

## Description

<b>MOUNTING</b>	Ceiling recessed
<b>LIGHT SOURCE</b>	LED
<b>OPTICAL SYSTEM</b>	Polished reflector + transparent cover (PRT)
<b>BEAM ANGLE</b>	72°
<b>LIGHT DISTRIBUTION</b>	Direct
<b>WIRING</b>	Electronic control gear FIX (ECG)
<b>MATERIALS</b>	Cover: transparent glass Diffuser: microprismatic PMMA Housing: die-cast aluminium Reflector: polished anodised aluminium Trim: die cast aluminium
<b>SURFACE FINISH</b>	Trim: white RAL 9003 (W03)
<b>VOLTAGE</b>	220-240 V, 50-60 Hz
<b>POWER FACTOR</b>	> 0,95
<b>NET LUMEN OUTPUT (Ta=25°C)</b>	3350 lm
<b>LUMINOUS FLUX TOLERANCE</b>	+/- 10 %
<b>POWER CONSUMPTION</b>	30 W
<b>SYSTEM EFFICACY</b>	112 lm/W
<b>CORRELATED COLOUR TEMPERATURE</b>	4000 K
<b>COLOUR RENDERING INDEX</b>	80 Ra
<b>COLOUR TOLERANCE</b>	3 SDCM
<b>EEC</b>	A++ / A+ / A
<b>PROTECTION CLASS</b>	II
<b>THERMAL MANAGEMENT</b>	Passive
<b>SERVICE LIFETIME (Ta=25°C)</b>	50,000 hours / L80 / B10
<b>AMBIENT OPERATING TEMPERATURE</b>	From -25 °C to +35 °C
<b>IP PROTECTION DEGREE</b>	IP65
<b>WARNING</b>	The luminaire is not suitable for use in outdoor applications
<b>DIMENSIONS</b>	Diameter - 251 mm, height - 101 mm
<b>OPENING</b>	Diameter - 232 mm
<b>WEIGHT</b>	2 kg

**AREAS OF APPLICATION** EDUCATION

## LIDC



-  HOSPITALITY
-  HOUSE AND FLAT
-  INDUSTRY AND ENGINEERING
-  HEALTH AND CARE
-  RETAIL AND PRESENTATION



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.