



PRODUCT DETAILS



Dimensions



Accessories



PRETTUS XTP

PRETTUS XTP POLISHED + OPAL LED
1650lm/840 1x19W, FIX, RAL 9003

DOWNLOADS

[Datasheet](#)
[Product sheet](#)
[Installation manual](#)
[IES file](#)
[LDT file](#)
[EEC](#)


Description

MOUNTING	Ceiling recessed
LIGHT SOURCE	LED
OPTICAL SYSTEM	Polished reflector + opal cover (PRO)
BEAM ANGLE	74°
LIGHT DISTRIBUTION	Direct
WIRING	Electronic control gear FIX (ECG)
MATERIALS	Diffuser: microprismatic PMMA Housing: die-cast aluminium Reflector: polished anodised aluminium Cover: opal glass
SURFACE FINISH	Trim: white RAL 9003 (W03)
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	1650 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	19 W
SYSTEM EFFICACY	87 lm/W
CORRELATED COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX	80 Ra
COLOUR TOLERANCE	3 SDCM
EEC	A++ / A+ / A
PROTECTION CLASS	II
THERMAL MANAGEMENT	Passive
SERVICE LIFETIME (Ta=25°C)	50,000 hours / L80 / B10
AMBIENT OPERATING TEMPERATURE	From -25 °C to +35 °C
IP PROTECTION DEGREE	IP65
WARNING	The luminaire is not suitable for use in outdoor applications
DIMENSIONS	Diameter - 251 mm, height - 101 mm
OPENING	Diameter - 232 mm
WEIGHT	2 kg

AREAS OF APPLICATION EDUCATION

HOSPITALITY

LIDC



- HOUSE AND FLAT
- INDUSTRY AND ENGINEERING
- HEALTH AND CARE
- RETAIL AND PRESENTATION



The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.