

ORDERING INFORMATION

CODE	DESCRIPTION	PRODUCT NUMBER	LED WATTAGE	CARTON QTY.	WEIGHT (NET/ GROSS)
01707	Twinspot Pro Black Emergency IP65 Luminaire	9336462017074	5.5 W	4	2.05 Kg / - Kg
01708	Twinspot Pro Emergency IP65 Luminaire (White)	9336462017081	5.5 W	4	2.05 Kg / - Kg

OPERATIONAL INFORMATION



GENERAL				BATTERY	
Voltage (V)	~220-240V	Mounting Type	Surface mounted (wall and ceiling)	Battery Type	LiFePO4
Frequency (Hz)	50 Hz	Duration	1/ 2/ 3/ 4/ 8 Hours (dependant on jumpers)	Battery Voltage	6.4 V
Max. Ambient Temp.	40°C			Battery Code(s)	01303
Class	I				
IP Rating	IP65			Charging Time	16 Hours
Wiring	Hard wired			Charger Operation	Smart

TOTAL POWER CONSUMPTION (TPC)

MODEL	MAINTAINED		NON - MAINTAINED	
	Max.	Avg.	Max.	Avg.
Twinspot Pro Emergency IP65 Luminaire (01707, 01708)	< 10 W	7.25 W	3 W	0.25 W

CONSTRUCTION AND DIMENSIONS

BODY	PC
DIFFUSER	PC
GEAR TRAY	Galvanized steel

TWINSLOT PRO EMERGENCY IP65


NOTE: For more information on the chemical resistance of our polycarbonate, please see the technical downloads page at ektor.com.au

ACCESSORIES AND SPARE PARTS

CODE	DESCRIPTION
01303	Battery 3000mAh 6.4V, 2 Cell LiFePO4
06118	Wireless daughterboard

Datasheet is subject to change without notice

Last updated: **28.August 2018_V1.6**