




# LEDFIRE LITE



## INCL. OUTER RING

The Ledfire Lite comes complete with an outer ring to suit hole sizes up to 130mm.



## FEATURES

- Fully compliant (AS/NZS 2293)
- Lithium batteries (LiFePO4)
- Recessed mount
- Emergency classification D50
- Average power consumption <0.45W

## ORDERING INFORMATION

CODE	PRODUCT CODE	DESCRIPTION	PRODUCT NUMBER	CARTON QTY
01696	EV-LED FIRE-LITE	Ledfire Lite Emergency Luminaire - D50	9336462016961	4
11405	EV-LED FIRE-LITE-B	Ledfire Lite Emergency Luminaire Black - D50	9336462114056	4


## OPERATIONAL INFORMATION

GENERAL				BATTERY	
Voltage	~230V	Emergency classification	D50	Battery type	LiFePO4
Frequency	50 Hz	Mounting type	Recessed mounting	Battery voltage	6.4 V
Ambient temp.	0 - 40°C	Wiring	Flex & plug	Battery code	01302
Class	2	Lamp power	2.7 W (D50)	Charging time	16 hours
Duration	90 / 120 min	Avg. circuit power	0.45 W	Charger type	Variable
IP rating	IP20	Max. circuit power	2.5 W		

## CONSTRUCTION AND DIMENSIONS

<b>BODY</b>	PC
<b>DISH</b>	PC
<b>CUT OUT*</b>	70 mm
<b>CUT OUT**</b>	75 - 130 mm

\* Size of inner ring  
\*\* Size of outer ring



**NOTE:** For more information on the chemical resistance of our polycarbonate, please see the technical downloads page at [ektor.com.au](http://ektor.com.au)

## SPACING TABLE (DISTANCE BETWEEN FITTINGS)

LUX	CLASSIFICATION	MOUNTING HEIGHT (M)															
		2.1	2.4	2.7	3	3.3	3.6	4	4.5	5	6	7	8	9	10	15	20
0.2	D50	18.0	18.7	19.4	20.1	20.7	21.2	21.8	22.5	23.2	24.2	24.9	25.4	25.7	25.9	23.7	15.2
0.5	D50	13.0	13.5	14.0	14.4	14.7	15.0	15.4	15.7	16.0	16.3	16.2	15.9	15.3	14.4		
1	D50	10.1	10.5	10.8	11.0	11.2	11.3	11.4	11.5	11.5	11.1	10.2	8.6	5.2			

Datasheet is subject to change without notice

Last updated: **03. September 2018\_V1.6**



Please view  
our website for  
**full datasheet**