



# LED FIRE PRO

A NEW ERA OF EMERGENCY MONITORING AND TESTING



## FEATURES

- Fully compliant (AS/NZS 2293)  
Recessed mount
- Premium Lithium batteries (LiFePO4) and smart charger
- Emergency classification D63
- Average power consumption <0.3W



## SELF TEST:

Commission the product to perform its own tests.



## DALI CERTIFIED:

Connect to a DALI system for DALI testing.



## SINGLE POINT UNIT:

Ektor products work as SPUs out of the box



## WIRELESS UPGRADE

Automatically test and sync data to the Cloud.

**ORDERING INFORMATION**

CODE	PRODUCT CODE	DESCRIPTION	PRODUCT NUMBER	CARTON QTY
01694	EV-LED FIRE-PRO	Ledfire Pro Emergency Luminaire, white	9336462016947	4
01697	EV-LED FIRE-PRO-B	Ledfire Pro Emergency Luminaire, black	9336462016978	4

**OPERATIONAL INFORMATION**

GENERAL				BATTERY	
Voltage	220~240V	Wiring	Flex & plug	Battery type	LiFePO4
Frequency	50 Hz	Duration	1 / 2 / 3 / 4 / 8 hours (dependant on jumpers)	Battery code	01303
Ambient temp.	0 - 40°C	Lamp codes	EV-LED FIRE-PRO-RD EV-LED FIRE-PRO-B-RD	Charging time	16 hours
Class	2			Charger type	Lithium
IP rating	IP20			Charger operation	Smart
Mounting type	Recessed mounting				

**EMERGENCY PERFORMANCE**

HOUR	1	2	3	4	8	CB
Lamp power (W)	4.3	4.3	2.9	2.5	1.4	3
Australian classification	D63	D63	D40	D32	D20	D40


**TOTAL POWER CONSUMPTION (TPC)**

MAINTAINED MODE		NON-MAINTAINED MODE	
Max.	Avg.	Max.	Avg.
7W	4.5W	3W	<0.25W

**CONSTRUCTION AND DIMENSIONS**

<b>BODY</b>	PC
<b>DISH</b>	PC
<b>CUT OUT**</b>	70 mm
<b>CUT OUT*</b>	75 - 100 mm

\*\* Size without outer ring  
\* Size with outer ring



**NOTE:** For more information on the chemical resistance of our polycarbonate, please see the technical downloads page at [ektor.com.au](http://ektor.com.au)

**ACCESSORIES LIST**

CODE	PRODUCT CODE	DESCRIPTION
06118	ZC-WIFI	Zencontrol Wireless Daughterboard
05304	ZC-ECM-DALI	Zencontrol - Easy Commissioning Module - D
00708	EV-STANDARD-1.2M-F&P	1.4m Flex and Plug (Standard)
00705	EV-CMS-2.4M-5PIN	2.4m CMS 5 Pin Plug Set
00706	EV-WAGO-2.4M-F&P	2.4m Wago Plug 5-P Blue WAGO 51110475
00707	EV-WIELAND-2.4M-F&P	2.4m Wieland Plug GST 1815S B1 ZRI S PB02
00709	EV-WIREDBYCLICK-2.4M-F&P	2.4m Wire by Click 5 Pin Lead L1025/5
00710	EV-CMS-2.4M-6PIN	2.4m CMS 6 Pin Plug Set

Datasheet is subject to change without notice

Last updated: **15. March 2017\_V1.0**



Please view  
our website for  
**full datasheet**