



## Features & Benefits

Available in 8W oval & 12W oval and round. Pre-selectable colour temperature 3000K / 4000K / 5000K. They also come with white and black trims

IP54 bulkhead suitable for internal use on walls or ceilings as well as external use on walls or ceilings not exposed to water

Polycarbonate construction which is impact resistant, and internally disguised screws to add security where needed. Double insulated, these do not require an earth.

## Applications

Residential  
Commercial  
Schools

## Lifetime

25,000hrs  
2 yr warranty



\* Box includes both black and white trims

230 V  
50 Hz

LED



IP  
54



For technical details, see page 2

## RX Basic Bulkhead

<b>WATTS</b>	8W Oval	12W Oval	12w Round
<b>LUMEN OUTPUT</b>	650lm	950lm	950lm
<b>EFFICACY</b>	81lm/W	79lm/W	79lm/W
<b>CCT &amp; RX</b>	3000K / 4000K / 5000K (TRI-COLOUR)		
<b>CRI</b>	Ra >80		
<b>BEAM ANGLE</b>	110°		
<b>IP RATING</b>	IP54		
<b>IK RATING</b>	IK08		
<b>IES FILES AVAILABLE?</b>	Yes		
<b>UGR</b>			
<b>DIMMING / CONTROLS / DRIVER</b>	Non-dimmable		
<b>LIFETIME</b>	25,000hrs		
<b>WARRANTY</b>	2 years		
<b>DIMENSIONS</b>	200mm x 100mm x 60mm	230mm x 105mm x 60mm	211mm x 211mm x 63mm
<b>WEIGHT</b>	220g	280g	440g
<b>POWER FACTOR</b>	0.5		
<b>VOLTAGE &amp; FREQUENCY</b>	230V 50		
<b>WORKING TEMP</b>	0°C ~+ 40°C		
<b>MATERIALS</b>	Polycarbonate		
<b>BODY COLOUR</b>	White + black trim *both included in the box		
<b>MOUNTING OPTIONS</b>	Ceiling / Wall		
<b>STANDARDS &amp; RATINGS EG CA</b>	AS/NZS 60598.2.1:2014		
<b>CONNECTION EG FLEX &amp; PLUG / TERMINAL</b>	Terminal block class II		

ORDER CODE	DESCRIPTION
REXBHD80VCCT	RX BULKHEAD 8W CCT OVAL
REXBHD120VCCT	RX BULKHEAD 12W CCT OVAL
REXBHD12RDCCT	RX BULKHEAD 12W CCT ROUND