



Features & Benefits

This fitting is packed with everything you want, high lumen output, dimmable, quality assurance, large terminals and rubber clip ends.

Three sizes available to suit a 90mm, 100mm, or 120mm cut out designed for new homes and to replace incandescent and compact fluorescent down lights in existing homes. Tilt option available.

Sourced to the standards you demand in a residential downlight this range makes traditional light sources a thing of the past when building homes.

Pre-selectable colour temperature, 3000k, 4000k & 5700k

Applications

Residential

Light Commercial

Lifetime

40,000hr

5 yr Warranty



For technical details, see page 2

RX Downlight

CODE	REXDL72CCTWH	REXDL92CCTWH	REXDL100CCTWH	REXDL120CCTWH	REXDL92TLTCCT
WATTS	7W	10W	13W	15W	10W
LUMEN OUTPUT	540lm +/- 4%	920lm +/- 4%	1090lm +/- 4%	1480lm +/- 4%	840lm +/- 4%
EFFICACY	77lm/w	92lm/w	84lm/w	98lm/w	84lm/w
CCT & RX	3000K / 4000K / 5700K (TRI-COLOUR)				
CRI	Ra > 80				
BEAM ANGLE	90°				
IP RATING	IP54				IP20
IK RATING	IK06				-
IES FILES AVAILABLE?	Yes				
UGR					
DIMMING / CONTROLS / DRIVER	YES				
LIFETIME	40,000hr				
WARRANTY	5 yr				
DIMENSIONS	85×39mm	110×38mm	120×45mm	145×45mm	104×30mm
CUTOUT	70-75mm	90-95mm	100-110mm	120-130mm	90mm
WEIGHT		250g	310g	460g	350g
POWER FACTOR	0.9				
VOLTAGE & FREQUENCY	230V 50/60Hz				
WORKING TEMP	0°C - + 45°C				
MATERIALS	Aluminium housing and PMMA diffuser				
BODY COLOUR	White				
MOUNTING OPTIONS	Recessed				
STANDARDS & RATINGS EG CA	AS/NZS 60598-2.2				
CONNECTION EG FLEX & PLUG / TERMINAL	Flex & Plug				

Photometric diagrams

ORDER CODE	DESCRIPTION
REXDL72CCTWH	DOWNLIGHT CCT 7W 90DEG DIA 72MM WHITE IP5
REXDL92CCTWH	DOWNLIGHT CCT 10W 90DEG DIA 110MM WHITE IP54
REXDL92TLTCCT	DOWNLIGHT CCT TILT 10W 90DEG DIA 104MM WHITE IP54
REXDL100CCTWH	DOWNLIGHT CCT 13W 90DEG DIA 120MM WHITE IP54
REXDL120CCTWH	DOWNLIGHT CCT 15W 90DEG DIA 145MM WHITE IP54

