



Features

Ultra slim profile fits seamlessly. Up to 80% energy saving compared to standard CFL. Long life time of 40,000hrs.
1200x300mm and 600x600mm available.

Benefits:

- Dali dimmable
- PMMA diffuser
- UGR19
- 4000K
- IP20 rated

Applications

Commercial, Retail, Hospital.

Lifetime

40,000hrs
3 yr warranty




For technical details, see page 2

RX LED Panel Product Range

WATTS	42w
LUMEN OUTPUT	3766lm to 3937lm
EFFICACY	89.7lm/W to 93.7lm/W
CCT & RX	4000k
CRI	>
BEAM ANGLE	80°
IP RATING	20
IK RATING	
IC RATING	N/A
IES FILES AVAILABLE?	Yes
UGR	19
DIMMING / CONTROLS / DRIVER	Dali
LIFETIME	40000hrs
WARRANTY	3 years
DIMENSIONS L,W,H	L295xW1195xH8mm and L595xW595xH8mm
CUTOUT	
POWER FACTOR	0.9
MATERIALS	Aluminium + PMMA diffuser
BODY COLOUR	White
MOUNTING OPTIONS	Recessed
STANDARDS & RATINGS EG CA	AS/NZS
CONNECTION EG FLEX & PLUG / TERMINAL	

ORDER CODE	DESCRIPTION
REXPL3012042WS1	RX LED PANEL 1200X300MM 42W 4K 3937LM UGR 19 DALI WHITE
REXPL606042WS1	RX LED PANEL 600X600MM 42W 4K 3766LM UGR 19 DALI WHITE

Photometric diagrams



Dimensions

