



Features

Slim Profile from only 40mm deep.

IP54 Suitable for use in Bathrooms. For indoor use only.

Dimmable and available in three wattages 12W, 18W, and 30W.

Sensor versions available in 12W & 18W

Colour correctable changeable (3000K, 4000K, 6000K) available in 18W & 30W.

Uniform light on the surface.

Up to 70% savings in energy compared to traditional lamps sources.

Easy Fix Bracket system allows for quick installation.

Benefits:

- Clips to support the gear tray during installation
- Quick connect gear tray
- Anti vandal clips
- Low glare diffuser

Applications

Residential, Commercial

Lifetime

40000 Hours

3 Year Guarantee



For technical details, see page 2

RX Selene Oyster

TYPE	Round	Square
WATTS	18w, 30w	12w, 18w, 30w
LUMEN OUTPUT	1,620lm - 2,900lm	1,400lm - 2,900lm
CCT & RX	3000K, 4000K	3000K, 4000K
CRI	80	80
BEAM ANGLE	N/A	N/A
IP RATING	IP54	IP54
IK RATING	IK08	IK08
IC RATING	N/A	N/A
IES FILES AVAILABLE?	Yes	Yes
UGR	N/A	N/A
DIMMING / CONTROLS / DRIVER	Triac dimmable	Triac dimmable
LIFETIME	40,000hrs L70 B10	40,000hrs L70 B10
WARRANTY	3 Years	3 Years
DIMENSIONS L,W,H	300mm x 40 mm 300 mm x 48 mm (CCT changeable version)	250mm x 250mm x 40 mm 300mm x 300mm x 40 mm 400mm x 400mm x 51 mm
MATERIALS	Polycarbonate	Polycarbonate
BODY COLOUR	White	White
MOUNTING OPTIONS	Surface	Surface
CONNECTION EG FLEX & PLUG / TERMINAL	Terminal	Terminal

ORDER CODE	DESCRIPTION
REXSEL12WCWSQ	RX SELENE OYSTER LED SQ DIM SEN 4000K
REXSEL12WWWSQ	RX SELENE OYSTER LED SQ DIM SEN 3000K
REXSEL18WCWMS	RX SELENE OYSTER LED RND DIM SEN 4000K
REXSEL18WWWMS	RX SELENE OYSTER LED RND DIM SEN 3000K
REXSEL18WCWSQD	RX SELENE OYSTER LED SQ DIM 4000K
REXSEL18WWWSQD	RX SELENE OYSTER LED SQ DIM 3000K
REXSEL30WCWSQD	RX SELENE OYSTER LED SQ DIM 4000K
REXSEL30WWWSQD	RX SELENE OYSTER LED SQ DIM 3000K
REXSEL18WCCTDIM	RX SELENE OYSTER LED 18W RND CCT DIM 300X48MM WHITE IP54
REXSEL30WCCTDIM	RX SELENE OYSTER LED 30W RND CCT DIM 300X48MM WHITE IP54