



Features

- Standard colour of Grey, other colours available on indent
- Integral Microwave sensor version with time delay and daylight to night and lux level switching
- Opal diffuser manufactured from a high impact polycarbonate with stainless steel Allen head trim fixing screws
- Tiltable LED tray for connection access
- The fitting has 4000K SMD (Surface mount diode) LED's mounted on a steel heat sink plate
- High specification driver with thermal & short circuit protection

Applications

Residential, hospitality, hotels, school.

Lifetime

25000hrs

5 yr warranty

Benefits:

- Choice of covers for most installation designs
- Integral Microwave sensor provides automatic switching when triggered but only when natural light is not sufficient. This ensures lighting is switched off when not required increasing energy savings
- Maximizes light output with low glare
- Strong and vandal resistant
- Uniform light output without dark or bright spots




For technical details, see page 2

RX Typhoon Product Range

WATTS	19w
LUMEN OUTPUT	1600lm
EFFICACY	84.2lm/W
CCT & RX	4000k
CRI	>
BEAM ANGLE	120°
IP RATING	65
IK RATING	08
IC RATING	N/A
IES FILES AVAILABLE?	Yes
UGR	
DIMMING / CONTROLS / DRIVER	Non Dimmable
LIFETIME	25000hrs
WARRANTY	5 years
DIMENSIONS L,W,H	350mm x 85mm
CUTOUT	
WEIGHT	
MATERIALS	
BODY COLOUR	Grey
MOUNTING OPTIONS	Wall Mount
STANDARDS & RATINGS EG CA	
CONNECTION EG FLEX & PLUG / TERMINAL	

ORDER CODE	DESCRIPTION
REXBHR19W4KG	RX TYPHOON BULKHEAD RND FLUSH 19W 4K IP65 GREY
REXBHR19W4KMG	RX TYPHOON BULKHEAD RND FLUSH 19W 4K M/WAVE SENSOR IP65 GREY

Photometric diagrams



Accessories




RX TYPHOON EYELID TRIM GREY
REXBHREYETRM



RX TYPHOON GRILLE TRIM GREY
REXBHRGRLTRM

Dimensions



Units = mm