


# SEVEN RING 106




with lower cover 090 and upper cover 1 or 2




## Description

Single, 70mm high and 106mm wide, pendant, surface and wall mounted ring luminaires for direct and direct-indirect illumination of representational areas, corridors, stairs, receptions and shops. Luminaires are made from rolled aluminium profile. In direct-indirect (D/I) version approximately 5% of light is emitted upwards through the holes in upper cover of the luminaire.

for direct illumination




for direct-indirect illumination



## Luminaire colour ("aa" in order code)

- 02** black RAL 9005 matt – on request
- 03** white RAL 9003 matt – on request
- 04** other RAL (must be specified) – on request
- 08** silver anodised - standard
- 09** silver RAL 9006 MS (microstructure) – on request

## Installation



## Lower optical part ("bbb" in order code)

- 090** matt opal cover

## Upper optical part ("y" in order code)

- 1** white painted solid steel reflector
- 2** white painted perforated steel reflector

## LED light source ("tt" in order code)

- 01** 930 - 3000K CRI >90 SDCM3
- 02** 940 - 4000K CRI >90 SDCM3
- 03** 830 - 3000K CRI >80 SDCM3
- 04** 840 - 4000K CRI >80 SDCM3


## Electrical equipment ("xx" in order code)

- 08** dimmable DALI LED driver

## Emergency unit (EM) ("ee" in order code)

- 00** without EM

## Order code




### 929-90-00650-0901-0408-0800

SEVEN RING 650/106 HI LED D, lower opal cover 090, upper white painted solid steel reflector, 4000K, CRI>80, silver anodised, dimmable DALI LED driver, without EM

### 929-91-00650-0902-0309-0800

SEVEN RING 650/106 LI LED D/I, lower opal cover 090, upper white painted perforated steel reflector, 3000K, CRI>80, silver RAL 9006 MS, dimmable DALI LED driver, without EM

▲ Example ▲



### SEVEN RING 106 HI LED

SEVEN RING 106 HI LED single luminaires, with high intensity LED light source, for direct and direct-indirect illumination, 106mm wide, dimmable DALI (xx=08) LED driver, 230V/50Hz, IP20, with one five-pole terminal block, with upper white painted solid (y=1) or perforated (y=2) steel reflector

Type	Order code		Luminaire		
	direct (D)	direct-indirect (D/I)	Φ (lm)	P (W)	D (mm)
<b>with cover</b>	<b>with OP cover 090</b>	<b>with OP cover 090</b>			
SEVEN RING 650/106 HI LED DALI	929-90-00650-0901	929-90-00650-0902	5460	54	650
SEVEN RING 950/106 HI LED DALI	929-90-00950-0901	929-90-00950-0902	8008	78	950
SEVEN RING 1250/106 HI LED DALI	929-90-01250-0901	929-90-01250-0902	10920	108	1250
SEVEN RING 1550/106 HI LED DALI	929-90-01550-0901	929-90-01550-0902	14560	142	1550
SEVEN RING 1850/106 HI LED DALI	929-90-01850-0901	929-90-01850-0902	16744	160	1850

### SEVEN RING 106 LI LED

SEVEN RING 106 LI LED single luminaires, with low intensity LED light source, for direct and direct-indirect illumination, 106mm wide, dimmable DALI (xx=08) LED driver, 230V/50Hz, IP20, with one five-pole terminal block, with upper white painted solid (y=1) or perforated (y=2) steel reflector

Type	Order code		Luminaire		
	direct (D)	direct-indirect (D/I)	Φ (lm)	P (W)	D (mm)
<b>with cover</b>	<b>with OP cover 090</b>	<b>with OP cover 090</b>			
SEVEN RING 650/106 LI LED DALI	929-91-00650-0901	929-91-00650-0902	2730	30	650
SEVEN RING 950/106 LI LED DALI	929-91-00950-0901	929-91-00950-0902	4004	40	950
SEVEN RING 1250/106 LI LED DALI	929-91-01250-0901	929-91-01250-0902	5460	55	1250
SEVEN RING 1550/106 LI LED DALI	929-91-01550-0901	929-91-01550-0902	7280	71	1550
SEVEN RING 1850/106 LI LED DALI	929-91-01850-0901	929-91-01850-0902	8372	81	1850

Luminous flux is stated for luminaires for direct illumination and light source 840.

Type of LEDs („tt“) and luminaire colour („aa“) must be specified when placing order.

### Accessories

To suspend the luminaire, it is necessary to order suspensions and power supply cable. For more information about accessories, please see page SEVEN and OITO accessories.

