

Item

R33H295-9016E2840L1S
sinus pendant luminaire di/ind white

General

LED LO 4000K 230W 30904lm
4 ring segments

Illuminant

EEI A+
Colour rendering index (CRI) > 80
Blue light hazard RG1 IEC 62471
MacAdam 3

Dimension

DMxH: 2950x100mm
ring section width 70 mm

Surface/Colour

aluminium
powdercoating white RAL9016 matte

Lens

satin polycarbonat diffuser
diffuser polycarbonate clear (id)

Protection rating



IP40 / Protection class I

Connection

230V 50/60Hz
incl. converter
8 suspension cables of 2000 mm with quick release
/ 3-pin connection-terminal with surface-mount
housing in white (DMxH: 74x21 mm)

Weight

35,0 kg



Product-Information

Brandnew high-class ring luminaire with LEDs in a compact lamp housing with a minimalistic and timeless design made of aluminium consist of 4 ring segments with a fine structure powder coating in white RAL9016 with a matte finish, for pendant mounting, designed for direct-indirect light emission. Installed by 8 suspension cables of 2000 mm with quick release, 3-pin connection-terminal with surface-mount housing in white (DMxH: 74x21 mm). Electrical connection through 3 used pins, in ceiling housing in white 74x21 mm (DMxH). Direct light emission through a satin polycarbonate diffuser for an almost homogeneous emission of light, and indirect through a transparent one. Luminaire equipped with the latest generation of LED boards with an efficiency of 134 lm per W, the innovative LED technology produces a luminous flux of 30904 lm with 230 W, colour temperature of 4000 K. Converter included. Colour Rendering Index (CRI) > 80, small colour tolerance MacAdam 3, Ingress Protection IP40, Protection Class I, Blue light hazard Risk Group RG = 1 IEC 62471. Rated lifetime of minimum 60.000 h [according to EU decree No. 1194/2012], Energy Efficiency Index (EEI) A+. Available with daylight and motion sensor. Dimensions DMxH: 2950x100 mm, ring section width 70 mm. Weight: 35,0 kg