

Item

T11H118-9016C2840X1L
skai pendant luminaire di/id white RAL9016

General

LED 4000K 51W 6580lm

Illuminant

LED

EEI A++

Colour rendering index (CRI) > 80

Blue light hazard RG0 IEC 62471

MacAdam 3

UGR < 16

Dimension

LxWxH: 1186x331x046mm

Surface/Colour

Material: Aluminium

Surface/Colour RAL9016 white fine matte finish

Lens

Lens technology

Diffuser PC satined (id)

Protection rating

IP20 / Protection class I

Connection

230V 50/60Hz



incl. converter

2 suspension cables 2000mm with quick release /

3-pin connection-terminal with surface-mount housing in white (100x100x31 mm)

Weight

7,5 kg



Product-Information

Super slim high-class pendant luminaire for office application designed for direct and indirect light emission, in special conical housing design with rounded corners and a visual height of 18 mm constructed out of an extruded aluminium section without screws (1 to adjust), with a fine structure powder coating in matte white 'RAL9016', a black decorative frame is here an option. This innovative luminaire is developed with a unique lens-technology for reduced brightness (LRA), an Unified Glare Rating (UGR) smaller than 16, a high efficiency of 129 lm per W and produces a luminous flux of 6580 lm with 51 W, colour temperature of 4000 K. Converter included and 3-pin connection-terminal with surface-mount housing in white (100x100x31 mm). Power supply cable in stylish solution, Colour Rendering Index (CRI) > 80, small Colour Tolerance MacAdam 3, Blue light hazard Risk Group RG0 IEC 62471, Rated lifetime of minimum 50.000 h [according to EU decree No. 1194/2012], Energy Efficiency Index (EEI) A++. Ingress Protection IP20, Protection Class I. LxWxH: 1186x331x046 mm. Weight: 7,5 kg