

Soft light is a new range of LED luminaires with excellent control of brightness to provide great visual comfort. Its characteristic design has made it an icon in fluorescent lighting, capable of exceptionally high performance.

Features

Steel housing. Painted white. Double parabolic aluminium with textured microlinear opal diffuser. Installation invisible ceilings and also in smooth non-modular with adapter frame.



Luxiona, Spain

Power

LED 36W

Beam

130° x 80°

Colour temperature

3000K warm white - CRI \geq 80
4000K neutral white - CRI \geq 80

Nominal lumen output

36W - 3800 lm

Control gear

Electronic (EL)
Electronic Dimmer Dali (ELDD)
Electronic (EL) + Emergency

IP

IP20 / 40

Supply voltage

220...240V, 50/60Hz

Installation

Installation invisible ceilings

Accessories

Adapter frame

Features




15mm. visible profile



25mm. visible profile


LED
 Recessed light using frame
 007/6060
 Difusor microlinear opal
LED and control gear included



36W
 130° x 80°
 control gear EL
 Drill 585x585
 3800 lm
 3000K **7730L/3683/16**
 4000K **7730L/3684/16**

36W
 130° x 80°
 control gear ELDD
 Drill 585x585
 3800 lm
 3000K **7730L/3683/16/D**
 4000K **7730L/3684/16/D**

36W
 130° x 80°
 control gear EL + emergency
 Drill 585x585
 3800 lm
 3000K **7730L/3683/16/E**
 4000K **7730L/3684/16/E**



Drill 610x610
007/6060

Adapter frame to install visible profile luminaire to a smooth non-modular.