

SPANDAU LED LED

1280lm, PC (fracture proof) clear, 840/4000K, extreme wide beam

Article No: 741 212

LED

IP
65

CE

RoHS

REACH


WEEE


UL

IK 08
PC



illustration may differ



 extreme wide beam

DIMENSIONS

L	B	H	a	b	max. weight
445 mm	164 mm	311 mm	260 mm	-	4.1 kg

DESCRIPTION

Wall surface-mounted luminaire for tunnels with driving speeds of 350 km/h with LED lamps. Luminaire housing made of weatherproof, fibreglass-reinforced polymer. Sealing system made of age resistant, form retaining silicone/synthetic rubber. Stainless steel wall bracket. Lamp spacing up to 17 m. Lamp diffuser with internal Fresnel lenses. Built-in transformer. Ready for connection through one M20 cable entry. Mounting including stainless steel wall bracket.

created on: 2019-01-22 (ext.) Subject to technical changes without prior notice

SPANDAU LED LED

1280lm, PC (fracture proof) clear, 840/4000K, extreme wide beam

Article No: 741 212

CHARACTERISTICS

Version	LED	Lamp power	1 x 10.8 W
Lamp	LED	System power	14 W
Lamp service life	L80 B10 > 60.000 h at +35°C	Colour temperature	White, 840/4000 K, Ra > 80
Extreme-temperature	-15°C to +35°C	Luminous flux lamp	1280 lm
Number of lamps	1-lamp	Protection class	II
Cover material	stainless steel	IP-rating	IP65
Colour housing	Stainless steel	Type of gear	Not required, 220 V - 240 V AC/DC, 0 Hz / 50-60 Hz
Cover	lamp cover	Through-wiring	without
Light distribution	extreme wide beam	Impact strength	IK08
ENEC / VDE	YESYES	Installation type	Surface mounting, wall mounting, single mounting

DIAGRAMS

