

PRODUCT FAMILY DATASHEET

SPOT FIREPROOF

Recessed mounted spotlight, round shape, fire-resistant



AREAS OF APPLICATION

- Replacement of halogen lamp spotlights
- Hotel rooms
- Bars, restaurants
- Bathrooms
- Accent lighting
- Galleries, museums
- General illumination
- Outdoor

PRODUCT BENEFITS

- High luminous efficacy
- Design matches the LEDVANCE DOWNLIGHT luminaire family
- Energy savings of up to 90 % compared to halogen lamp spotlights
- Functional and minimalistic design
- Easy installation with fast connection
- External driver for extended flexibility (compatible with selected dim. drivers)
- Designed for extra IP protection

PRODUCT FEATURES

- Fire-resistant (up to 90 minutes, tested in accordance with EN 1365-2:2014 'fire resistance tests for loadbearing elements - Part 2: Floors and roofs')
- Outdoor use and fire-resistant (up to 90 minutes, BS476-20:1987 and BS476-21:1987)
- Compatible with standard ceiling cutouts of 68 mm
- Initial color consistency: ≤ 4 SDCM




- Type of protection, front side: IP65

TECHNICAL DATA

Product description	Electrical data			Photometrical data			Light technical data	Dimensions & weight			
	Nominal wattage	Nominal voltage	Mains frequency	Luminous flux	Light color (designation)	Color rendering index Ra	Beam angle	Diameter	Height	Product weight	Mounting diameter
SPOT FP FIX 7 W 3000 K IP65 WT	7.00 W	220...240 V	50/60 Hz	530 lm	Warm White	>80	38 °	90.0 mm	72.0 mm	289.00 g	68 mm

Product description	Colors & materials		Temperatures & operating conditions	Lifespan			Capabilities	
	Body material	Product color	Ambient temperature range	Lifespan L70 at 25 °C	Lifespan L80 at 25 °C	Lifespan L90 at 25 °C	Dimmable	Type of connection
SPOT FP FIX 7 W 3000 K IP65 WT	Aluminum	White	-20...45 °C	50000 h	40000 h	20000 h	No	Screw terminal, 2-Pole (L,N)

Product description	Certificates & standards	
	Protection class	Type of protection
SPOT FP FIX 7 W 3000 K IP65 WT	II	IP65



SPOT FP FIX 7 W 3000 K IP65 WT

SPOT FP FIX 7 W 3000 K IP65 WT

APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075127333	SPOT FP FIX 7 W 3000 K IP65 WT	Shipping carton box 20	525 mm x 400 mm x 250 mm	52.50 dm ³	8720.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see
 ▶ www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.