

PRODUCT FAMILY DATASHEET

SPOT MULTI 2x30W

Recessed mounted spotlight, swivelable with two spot



AREAS OF APPLICATION

- Accent- and general lighting for all kind of salesrooms
- Fashion shops, accessories shops
- Shops, boutiques
- Hotel rooms
- Cafés

PRODUCT BENEFITS

- Low flicker light thanks to special electronic control gear
- High luminous efficacy
- Covering against other ceiling installations thanks to closed sheet steel housing
- Easy replacement of external driver thanks plug with bayonet lock
- Functional and minimalistic design
- 5 years guarantee

PRODUCT FEATURES

- Large faceted reflector for high light output
- Beam angle: 38°
- Gimbal adjustment angle: +/- 25°






TECHNICAL DATA

Product description	Electrical data			Luminaire control gear data				
	Nominal wattage	Nominal voltage	Mains frequency	ECG - Length	ECG - Width	Max. no. of lum. on circuit break. B16 A	Max. no. of lum. on circuit break. C10 A	Max. no. of lum. on circuit break. C16 A
SPOT MULTI 2 x 30W 3000K FL WT/BK	2*30 W	220...240 V	50/60 Hz	113 mm	40 mm	16	13	20
SPOT MULTI 2 x 30W 4000K FL WT/BK	2*30 W	220...240 V	50/60 Hz	113 mm	40 mm	16	13	20

Product description	Photometrical data				Light technical data	Dimensions & weight				Colors & materials	
	Luminous flux	Light color (designation)	Color rendering index Ra	Beam angle		Length	Width	Height	Product weight	Body material	Product color
SPOT MULTI 2 x 30W 3000K FL WT/BK	2*2700 lm	Warm White	>80	38.00 °		330.0 mm	173.0 mm	135.0 mm	2700.00 g	Aluminum	White
SPOT MULTI 2 x 30W 4000K FL WT/BK	2*2700 lm	Cool White	>80	38.00 °		330.0 mm	173.0 mm	135.0 mm	2700.00 g	Aluminum	White

Product description	Cover material	Temperatures & operating conditions	Lifespan			Capabilities	
		Ambient temperature range	Lifespan L70 at 25 °C	Lifespan L80 at 25 °C	Lifespan L90 at 25 °C	Adjustable	Dimmable
SPOT MULTI 2 x 30W 3000K FL WT/BK	Polymethylmethacrylate (PMMA)	-10...40 °C	50000 h	45000 h	30000 h	Yes	No
SPOT MULTI 2 x 30W 4000K FL WT/BK	Polymethylmethacrylate (PMMA)	-10...40 °C	50000 h	45000 h	30000 h	Yes	No

Product description	Type of connection	Certificates & standards	
		Protection class	Type of protection
SPOT MULTI 2 x 30W 3000K FL WT/BK	Screw terminal, 2-Pole (L,N)	II	IP20
SPOT MULTI 2 x 30W 4000K FL WT/BK	Screw terminal, 2-Pole (L,N)	II	IP20



SPOT MULTI 2 x 30W 3000K FL WT/BK,
SPOT MULTI 2 x 30W 4000K FL WT/BK

SPOT MULTI 2 x 30W 3000K FL WT/BK

SPOT MULTI 2 x 30W 4000K FL WT/BK

EQUIPMENT / ACCESSORIES

– Driver included

APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075113961	SPOT MULTI 2 x 30W 3000K FL WT/BK	Shipping carton box 4	720 mm x 220 mm x 365 mm	57.82 dm ³	11996.00 g
4058075113985	SPOT MULTI 2 x 30W 4000K FL WT/BK	Shipping carton box 4	720 mm x 220 mm x 365 mm	57.82 dm ³	11996.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see

▶ www.ledvance.com/guarantee

DISCLAIMER

— Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.