

8 885 056 049

Superlight LED 1, asymmetrical beam




With 26 W high performance LED module (Zhaga), 3000 K

protection class I, IP67, ENEC, IK08

Leuchtengehäuse aus Aluminium-Druckguss AlSi12 (Leg. 230), highly efficient reflector, polyester powder coated by high-quality, UV-stabilized coating process, all exterior parts are stainless steel, tempered safety glass, non-reflective coating on one side, silicon gasket, mounting bracket powder coated aluminium: 2 drilled holes Ø 7 mm, spacing 50-70 mm, 1 centre hole Ø 17 mm, tilt range 180°, M20 cable gland, cable gland: M20, integral driver (AC/DC),

CRI min 80, 2 SDCM, Service life L: 90, B:10 > 50.000 h

| Part number | Colour | Light source | Weight | Main beam angle |
|---------------|-------------|--|---------|-----------------|
| 8 885 056 049 | silver grey | 26 W high performance LED module (Zhaga), 3000 K | 2,40 kg | 45° |





| Part number | Colour | Description |
|----------------|-------------|---|
| 1 28 0 792 950 | silver grey | Cowl aluminium, to avoid glare from 3 directions |



| Part number | Colour | Description |
|----------------|-------------|---|
| 1 28 0 797 950 | silver grey | Barn doors aluminium, to avoid glare from 4 directions, variable control of light distribution |



| Part number | Colour | Description |
|----------------|-------------|--|
| 1 28 0 802 950 | silver grey | Vertical louvre stainless steel, to prevent lateral glare |



| Part number | Description |
|-------------|---|
| 1 28 0 810 | Honeycomb louvre internally fitted, to avoid glare |