

LED Satellite Surface Mount – Corridor



CAT NO. 659508/LI, 659509/LI, 659510/LI, 659511/LI



659508/LI

Specifications		
Cat No	659508/LI, 659510/LI	659509/LI, 659511/LI
Finish	White	Black
Battery pack	Li-ion 6.4V, 3.0Ah	
Operating Voltage	240V a.c. +/- 6% 50Hz	
Power Consumption	2W	
Body Constructions	Polycarbonate (satellite head), steel (enclosure)	
Operating Temperature	10° to 40°	
IP Rating	IP20	
Compliance	AS/NZS 2293 AS/NZS 60598  	

# LED Satellite Surface Mount – Corridor

CAT NO. 659508/LI, 659509/LI, 659510/LI, 659511/LI

- iSmart™ temperature sensing technology for the LIION battery
- Electronics designed to lengthen the life of the battery, minimising maintenance costs
- Environmentally friendly battery
- Easy to install
- One high Brightness LED
- SPU or Axiom options
- 5 year warranty
- Designed and manufactured in Australia

Cat No	Description	Classification C <sub>0</sub> /C <sub>90</sub>
659508/LI	LED Satellite Surface Mount White	D80/E16
659509/LI	LED Satellite Surface Mount Black	D80/E16
659510/LI	Axiom LED Satellite Surface Mount White	D80/E16
659511/LI	Axiom LED Satellite Surface Mount Black	D80/E16


### Spacing table:

Maximum spacings between luminaires for 0.2 lux



Mounting Height (m)	2.4	2.7	3	3.3	3.6	4.0
A	22.0	22.8	23.6	24.3	25.0	25.8
B	9.2	9.8	10.6	11.0	11.6	12.2

Maximum spacings between luminaires for 1 lux

Mounting Height (m)	2.4	2.7	3	3.3	3.6	4.0
A	12.5	12.9	13.2	13.5	13.8	14
B	6.1	6.3	6.5	6.5	6.5	6.4



### DIMENSIONS



Legrand - Australia  
1300 369 777  
www.legrand.com.au  
ABN 31 000 102 661

Legrand - New Zealand  
0800 476 009  
www.legrand.co.nz

Refer to your group buying office, Legrand Sales Representative or Legrand Sales Office for pricing.

Please note: specifications are subject to change without prior notice.