

PRODUCT DATASHEET

LDPFM BATTEN 600 20 W 3000 K 4000 5000 Blade

LED PERFORMANCE TRI COLOUR BATTEN | LED batten luminaires with slide switch for adjusting one of selectable light colors



AREAS OF APPLICATION

- Offices
- Commercial lighting
- Storage rooms

PRODUCT BENEFITS

- Homogeneous light output
- Mercury-free technology
- Slim housing

PRODUCT FEATURES

- Uniform illumination
- Three light colors selectable via slide switch
- Color rendering index R_a : > 80
- Beam angle: 110°
- Type of protection: IP20
- Protection class: I
- Power factor: > 0.9



TECHNICAL DATA

Electrical data

Nominal wattage	20.00 W
Operating mode	Integrated LED driver
Nominal voltage	220...240 V
Mains frequency	50 Hz

Photometrical data

Color temperature	3000/4000/5000 K
Color rendering index Ra	80
Light color (designation)	Warm White/Cool White/Daylight
Luminous flux	2000/2200 lm
Luminous efficacy	100.0/110 lm/W

Dimensions & weight

Length	600.0 mm
Width	75.0 mm
Height	31.0 mm
Product weight	320.00 g

Colors & materials

Body material	Aluminum
Housing color	White
Product color	White
Cover material	Polycarbonate (PC)

Temperatures & operating conditions

Ambient temperature range	-20...45 °C
---------------------------	-------------

Additional product data

Mounting type	Surface
Mounting location	Ceiling / Wall

Capabilities

Dimmable	No
Type of connection	Terminal

Certificates & standards

Protection class	I
Type of protection	IP20

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075207448	Folding carton box 1	607 mm x 80 mm x 35 mm	381.00 g	1.70 dm ³
4058075207455	Shipping carton box 10	630 mm x 205 mm x 185 mm	4407.00 g	23.89 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.