

# PRODUCT DATASHEET

## LDPFM BATTEN 1200 40 W 3000 K 4000 5700 Narrow

**LED PERFORMANCE TRI COLOUR BATTEN | LED batten luminaires with slide switch for adjusting one of selectable light colors**



---

### AREAS OF APPLICATION

- Offices
- Commercial lighting
- Storage rooms

---

### PRODUCT BENEFITS

- Homogeneous light output
- Mercury-free technology
- Slim housing

---

### PRODUCT FEATURES

- Uniform illumination
- Three light colors selectable via slide switch
- Color rendering index  $R_a$ : > 80
- Beam angle: 110°
- Type of protection: IP20
- Protection class: I
- Power factor: > 0.9



---

**TECHNICAL DATA****Electrical data**

Nominal wattage	40.00 W
Operating mode	Integrated LED driver
Nominal voltage	220...240 V
Mains frequency	50/60 Hz

**Photometrical data**

Color temperature	3000/4000/5700 K
Color rendering index Ra	80
Light color (designation)	Warm White/Cool White/Daylight
Luminous flux	4200 lm
Luminous efficacy	105 lm/W

**Dimensions & weight**

Length	1165 mm
Width	60.0 mm
Height	60.0 mm
Product weight	1900.00 g

**Colors & materials**

Body material	Polyvinyl chloride (PVC)/POL
Housing color	White
Product color	White

**Temperatures & operating conditions**

Ambient temperature range	-10...40 °C
---------------------------	-------------

**Additional product data**

Mounting type	Surface
Mounting location	Ceiling / Wall

**Capabilities**

Dimmable	No
Type of connection	Terminal

**Certificates & standards**

Protection class	I
Type of protection	IP20

---

**LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075217898	Folding carton box 1	1185 mm x 70 mm x 65 mm	2142.00 g	5.39 dm <sup>3</sup>
4058075217904	Shipping carton box 6	1200 mm x 225 mm x 150 mm	13864.00 g	40.50 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.