

Datasheet

WP2 LED Weatherproof Batten IP65 - Axiom



CAT NO. 685060, 685090



685060



685090


Cat No	685060	685090
Description	WP2L6 LED BATTEN 4K MTD AXIOM	WP2L12 LED BATTEN 4K MTD AXIOM
Operation Mode	Maintained	
Classification C0/C90	C0: D80, C90: D20	C0: D160, C90: D40
Charging Current (High rate)	150mA	300mA
Charging Current (Low rate)	38mA	75mA
Length (mm)	671	1273
Weight (kg)	2.7	4.8
Light source	LED	
Luminaire luminous flux (lm)	2,100	4,100
Circuit power (W)	34	64
Luminaire efficacy (lm/W)	62	64
Power factor	>0.9	
Supply voltage	240V 50Hz	
Ballast type	Fixed output / Non-Dimmable	
Operating temperature	0°C to 40°C	
IP rating	IP65	
Retaining clips	316 Stainless Steel	
Body construction	Moulded glass reinforced polyester (GRP)	
Diffuser	Clear reeded polycarbonate	
Gasket	Silicone	
Geartray	High reflective white powder coated mild steel	
Compliance	AS/NZS 2293, AS/NZS 60598  	

WP2 LED Weatherproof Batten IP65 - Axiom

CAT NO. 685060, 685090



- A premium range of LED weatherproof battens
- Available in 2 foot or 4 foot lengths
- Two lumen packages: 2100lm or 4100lm, 4000K colour temperature
- Ideal replacement for T5 equivalents
- Dedicated LED engine for maximum spacings
- LED useful life of 50,000 hours L70 at ambient temperature up to 40°C
- CRI > 80
- IP65 rated
- Wireless maintained emergency



Replacement Batteries		
Qty	Cat No	Description
1	686244	Battery pack 2 x 5 Sub C 1.5 Ah NiCd for WP2L6
2	686244	Battery pack 2 x 5 Sub C 1.5 Ah NiCd for WP2L12

Legrand - AUS
1300 369 777
www.legrand.com.au
ABN 31 000 102 661

Legrand - NZ
0800 476 009
www.legrand.co.nz

Refer to your group buying office, Legrand Sales Representative or
Legrand Sales Office for pricing.

LEG2236

08_2018