

ZUG LED m1500

6570lm, PC Tropol® (fracture proof), 840/4000K, medium beam


Article No: 775 680 34 84 - MC5

LED


EL IP 66 IP 67 IP 68 20m IP 69K CE     IK 10 PC



illustration may differ



 XARA® (optional)

 medium beam

DIMENSIONS

L	B	H	a	b	max. weight
1710 mm	88 mm	97 mm	1610 mm	-	4.9 kg

DESCRIPTION

Tubular luminaire with LED lamps, resistant to pressurised water. Polymer luminaire tube (Ø 75 mm). With internal, anodised aluminium reflector. Excentric locking technology for easy opening with retractable handle on face side. With hexagon socket screw to prevent unauthorised opening. Ready for connection via two face side cable glands M20 and through-wiring. Mounting with two stainless steel/polymer mounting clamps. Variable mounting distance.

created on: 2018-11-21 (ext.) Subject to technical changes without prior notice

ZUG LED m1500

6570lm, PC Tropol® (fracture proof), 840/4000K, medium beam

Article No: 775 680 34 84 - MC5

CHARACTERISTICS

Version	m1500	Lamp power	1 x 41 W
Lamp	LED	System power	44 W
Lamp service life	L80 B10 > 60.000 h at +40°C	Colour temperature	White, 840/4000 K, Ra > 80
Extreme-temperature	-25°C to +40°C	Luminous flux lamp	6570 lm
Number of lamps	1-lamp	Protection class	II
Cover material	polymer	IP-rating	IP66, IP67, IP68 20m, IP69K
Colour housing	None	Type of gear	LED operating device current-controlled, Not dimmable, 220 V - 240 V AC/DC
Cover	PC Tropol® (fracture proof)	Through-wiring	4 x 1,5 mm ²
Light distribution	medium beam	Impact strength	IK10
Manufacturer warranty	5 years	Installation type	wire suspension, Cable suspension, ceiling mounting, wall mounting, single mounting, row mounting
ENEC / VDE	YESYES		
EL (Emergency Lighting)	optional		

DIAGRAMS

