

ZUG LED m600

2630lm, PMMA Transopal® (impact strengthened), 840/4000K, medium beam

Article No: 775 280 34 24 - MC7

LED

EL IP 66 IP 67 IP 68 20m IP 69K CE





illustration may differ



XARA® (optional)

medium beam

DIMENSIONS

L	B	H	a	b	max. weight
800 mm	88 mm	97 mm	700 mm	-	2.7 kg

DESCRIPTION

Tubular luminaire with LED lamps, resistant to pressurised water. Polymer luminaire tube (Ø 75 mm). With internal, anodised aluminium reflector. Eccentric locking technology for easy opening with retractable handle on face side. With hexagon socket screw to prevent unauthorised opening. Ready for connection via two face side cable glands M20 and through-wiring. Mounting with two stainless steel/polymer mounting clamps. Variable mounting distance.

created on: 2018-10-17 (ext.) Subject to technical changes without prior notice

ZUG LED m600

2630lm, PMMA Transopal® (impact strengthened), 840/4000K, medium beam

Article No: 775 280 34 24 - MC7

CHARACTERISTICS

Version	m600	Lamp power	1 x 16 W
Lamp	LED	System power	19 W
Lamp service life	L80 B10 > 60.000 h at +40°C	Colour temperature	White, 840/4000 K, Ra > 80
Extreme-temperature	-25°C to +40°C	Luminous flux lamp	2630 lm
Number of lamps	1-lamp	Protection class	II
Cover material	polymer	IP-rating	IP66, IP67, IP68 20m, IP69K
Colour housing	None	Type of gear	LED operating device current-controlled, Not dimmable, 220 V - 240 V AC/DC
Cover	PMMA Transopal® (impact strengthened)	Through-wiring	4 x 1,5 mm ²
Light distribution	medium beam	Impact strength	IK09
Manufacturer warranty	5 years	Installation type	wire suspension, Cable suspension, ceiling mounting, wall mounting, single mounting, row mounting
ENEC / VDE	YESYES		
EL (Emergency Lighting)	optional		

DIAGRAMS

