



PRODUCT DETAILS



UPCOMING NEW FAST RUNNER UPDATED PHASE-OUT PRODUCTS



Accessories



DOWNLOADS

[Datasheet](#)

[Installation manual](#)

AIRN T

Description

| | |
|--------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| MOUNTING | Ceiling surfaced (SFD) Suspended (SSD) |
| LIGHT SOURCE | LED |
| OPTICAL SYSTEM | Opal diffuser (OPD) |
| LIGHT DISTRIBUTION | Direct |
| WIRING | Electronic control gear FIX / DALI (ECG / EDA) Emergency unit variant (3H) External lead-in flexible cable (SSD) |
| MATERIALS | Diffuser: opal PMMA Housing: extruded aluminium Rope suspension 1,5 m (suspended version) |
| SURFACE FINISH | Housing: grey RAL 9006 (G06) |
| SERVICE LIFETIME (Ta=25°C) | 50,000 hours / L80 / B10 |
| AMBIENT OPERATING TEMPERATURE | From -20 °C to +35 °C (from 5 °C with EM unit) |

- AREAS OF APPLICATION**
- ARCHITECTURE AND MEDIA
 - EDUCATION
 - RETAIL AND PRESENTATION



List of products

| PRODUCT NAME | STATUS | QUICK DOWNLOADS |
|----------------------------------------------------------------|--------|-----------------------------------------------------------------------------------------------------------------|
| AIRN T S SFD OPAL LED 6300lm/830 1x116W, FIX, RAL 9006 | | RFA / 3DS / IES / LDT / CURVE / |
| AIRN T S SFD OPAL LED 6600lm/840 1x116W, FIX, RAL 9006 | | RFA / 3DS / IES / LDT / CURVE / |
| AIRN T M SFD OPAL LED 7850lm/830 1x146W, FIX, RAL 9006 | | RFA / 3DS / IES / LDT / CURVE / |
| AIRN T M SFD OPAL LED 8150lm/840 1x146W, FIX, RAL 9006 | | RFA / 3DS / IES / LDT / CURVE / |
| AIRN T S SFD OPAL LED 6300lm/830 1x116W, DALI, RAL 9006 | | RFA / 3DS / IES / LDT / CURVE / |
| AIRN T S SFD OPAL LED 6600lm/840 1x116W, DALI, RAL 9006 | | RFA / 3DS / IES / LDT / CURVE / |
| AIRN T M SFD OPAL LED 7850lm/830 1x146W, DALI, RAL 9006 | | RFA / 3DS / IES / LDT / CURVE / |
| AIRN T M SFD OPAL LED 8150lm/840 1x146W, DALI, RAL 9006 | | RFA / 3DS / IES / LDT / CURVE / |
| AIRN T S SFD OPAL LED 6300lm/830 1x116W, FIX + EM 3H, RAL 9006 | | RFA / 3DS / IES / LDT / CURVE / |
| AIRN T S SFD OPAL LED 6600lm/840 1x116W, FIX + EM 3H, RAL 9006 | | RFA / 3DS / IES / LDT / CURVE / |
| AIRN T M SFD OPAL LED 7850lm/830 1x146W, FIX + EM 3H, RAL 9006 | | RFA / 3DS / IES / LDT / CURVE / |
| AIRN T M SFD OPAL LED 8150lm/840 1x146W, FIX + EM 3H, RAL 9006 | | RFA / 3DS / IES / LDT / |

| | |
|----------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| AIRN T S SSD OPAL LED 6300lm/830 1x116W, FIX, RAL 9006 | CURVE / RFA / 3DS / IES / LDT / CURVE / |
| AIRN T S SSD OPAL LED 6600lm/840 1x116W, FIX, RAL 9006 | RFA / 3DS / IES / LDT / CURVE / |
| AIRN T M SSD OPAL LED 7850lm/830 1x146W, FIX, RAL 9006 | RFA / 3DS / IES / LDT / CURVE / |
| AIRN T M SSD OPAL LED 8150lm/840 1x146W, FIX, RAL 9006 | RFA / 3DS / IES / LDT / CURVE / |
| AIRN T S SSD OPAL LED 6300lm/830 1x116W, DALI, RAL 9006 | RFA / 3DS / IES / LDT / CURVE / |
| AIRN T S SSD OPAL LED 6600lm/840 1x116W, DALI, RAL 9006 | RFA / 3DS / IES / LDT / CURVE / |
| AIRN T M SSD OPAL LED 7850lm/830 1x146W, DALI, RAL 9006 | RFA / 3DS / IES / LDT / CURVE / |
| AIRN T M SSD OPAL LED 8150lm/840 1x146W, DALI, RAL 9006 | RFA / 3DS / IES / LDT / CURVE / |
| AIRN T S SSD OPAL LED 6300lm/830 1x116W, FIX + EM 3H, RAL 9006 | RFA / 3DS / IES / LDT / CURVE / |
| AIRN T S SSD OPAL LED 6600lm/840 1x116W, FIX + EM 3H, RAL 9006 | RFA / 3DS / IES / LDT / CURVE / |
| AIRN T M SSD OPAL LED 7850lm/830 1x146W, FIX + EM 3H, RAL 9006 | RFA / 3DS / IES / LDT / CURVE / |
| AIRN T M SSD OPAL LED 8150lm/840 1x146W, FIX + EM 3H, RAL 9006 | RFA / 3DS / IES / LDT / CURVE / |

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.