

atomⁱ

LED FLOODLIGHTS

20W Slim flood light

AT9819/20



Features

- Ideal for outdoor residential applications
- Supplied with integral driver
- Compact and robust design
- Three year warranty



Colour temperature

Daylight



Finish

Black and white



IP Rating

IP65 and IP44



Rated Wattage

20W

Product datasheet

Description

20W Slim flood light.

Finish



Black (BLK)



White (WH)

Product specification

| | | |
|----------------------------------|---------------------------------|--------------------|
| Voltage | 230V~ 50Hz | |
| Power consumption | 20W | |
| | Without sensor | With sensor |
| Light colour options | Day light (DL) | Day light (DL) |
| Lumen output | 1835lm | 1690lm |
| Colour temperature | 5000K | 5000K |
| Beam Angle | 120° | |
| Dimmable | No | |
| Warranty | 3 years | |
| Colour rendering index | ≥ 80 | |
| Working temperature | 40°C | |
| IP Rating | IP65 | IP44 |
| Electrical classification | Class I | |
| Sensor | | |
| Detection range | 12m (at 1.8m mounting height) | |
| Duration time adjustment | (10±5) seconds to (4±1) minutes | |
| Detection circuitry | Passive infra-red (PIR) | |

Product range

| Code | Finish | Colour temperature |
|-----------------|--------|--------------------|
| AT9819/20/BLK | Black | Daylight |
| AT9819/20/BLK/S | Black | Daylight |
| AT9819/20/WH | White | Daylight |
| AT9819/20/WH/S | White | Daylight |

Dimensions

| Wattage | Width | Height | Depth |
|-----------------|-------|--------|-------|
| AT9819/20/BLK | 160mm | 128mm | 41mm |
| AT9819/20/BLK/S | 160mm | 176mm | 46mm |
| AT9819/20/WH | 160mm | 128mm | 41mm |
| AT9819/20/WH/S | 160mm | 176mm | 46mm |

