



Features & Benefits

Available in 8W oval & 12W oval and round. Pre-selectable colour temperature 3000K / 4000K / 5000K. They also come with white and black trims

IP54 bulkhead suitable for internal use on walls or ceilings as well as external use on walls or ceilings not exposed to water

Polycarbonate construction which is impact resistant, and internally disguised screws to add security where needed. Double insulated, these do not require an earth.

Applications

Residential
Commercial
Schools

Lifetime

25,000hrs
2 yr warranty



* Box includes both black and white trims

230 V
50 Hz

LED



IP
54



For technical details, see page 2

RX Basic Bulkhead

WATTS	8W Oval	12W Oval	12w Round
LUMEN OUTPUT	650lm	950lm	950lm
EFFICACY	81lm/W	79lm/W	79lm/W
CCT & RX	3000K / 4000K / 5000K (TRI-COLOUR)		
CRI	Ra >80		
BEAM ANGLE	110°		
IP RATING	IP54		
IK RATING	IK08		
IES FILES AVAILABLE?	Yes		
UGR			
DIMMING / CONTROLS / DRIVER	Non-dimmable		
LIFETIME	25,000hrs		
WARRANTY	2 years		
DIMENSIONS	200mm x 100mm x 60mm	230mm x 105mm x 60mm	211mm x 211mm x 63mm
WEIGHT	220g	280g	440g
POWER FACTOR	0.5		
VOLTAGE & FREQUENCY	230V 50		
WORKING TEMP	0°C ~+ 40°C		
MATERIALS	Polycarbonate		
BODY COLOUR	White + black trim *both included in the box		
MOUNTING OPTIONS	Ceiling / Wall		
STANDARDS & RATINGS EG CA	AS/NZS 60598.2.1:2014		
CONNECTION EG FLEX & PLUG / TERMINAL	Terminal block class II		

ORDER CODE	DESCRIPTION
REXBHD80VCCT	RX BULKHEAD 8W CCT OVAL
REXBHD120VCCT	RX BULKHEAD 12W CCT OVAL
REXBHD12RDCCT	RX BULKHEAD 12W CCT ROUND