

# Datasheet



## WP2 LED Weatherproof Batten IP65 – DALI Emergency




CAT NO. **685050/D**, **685080/D**



**685050/D**



**685080/D**

Cat No	<b>685050/D</b>	<b>685080/D</b>
Description	WP2L6 LED BATTEN 4K MTD	WP2L12 LED BATTEN 4K MTD
Operation Mode	Switched Maintained	
Classification C0/C90	C0: D100, C90: C80	C0: D80, C90: D20
Length (mm)	671	1273
Weight (kg)	2.7	4.8
Light source	LED	
Luminaire luminous flux (lm)	2,100	4,100
Energy consumption (excluding emergency pack)	4.8W hrc / 2.5W lrc	
Luminaire efficacy (lm/W)	62	64
Power factor	>0.9	
Supply voltage	240V 50Hz	
Ballast type	Fixed output/Non-Dimmable	
Operating temperature	0°C to 40°C	
IP rating	IP65	
Retaining clips	316 Stainless Steel	
Body construction	Moulded glass reinforced polyester (GRP)	
Diffuser	Clear reeded polycarbonate	
Gasket	Silicone	
Geartray	High reflective white powder coated mild steel	
Compliance	IEC 62385 AS/NZS 60598   	

\*hrc - high rate charge, lrc - low rate charge.


# Datasheet



## WP2 LED Weatherproof Batten IP65 – DALI Emergency

CAT NO. **685050/D, 685080/D**

- A premium range of LED weatherproof battens
- Available in 2 foot or 4 foot lengths
- Maintained emergency
- Two lumen packages: 2100lm or 4100lm, 4000K colour temperature
- Ideal replacement for T5 equivalents
- Dedicated LED engine for maximum spacings
- LED useful life of 50,000 hours L70 at ambient temperature up to 40°C
- CRI > 80
- IP65 rated



Legrand Australia  
1300 369 777  
[www.legrand.com.au](http://www.legrand.com.au)  
ABN 31 000 102 661

Legrand New Zealand  
0800 476 009  
[www.legrand.co.nz](http://www.legrand.co.nz)

Refer to your group buying office, Legrand Sales Representative or Legrand Sales Office for pricing.

Please note: specifications are subject to change without prior notice.

LEG2241

08\_2018