Data Sheet

Weatherproof LED Exit Sign DALI Emergency



CAT NO. 684650/D, 684651/D, 684652/D, 684670/D, 684671/D, 684672/D





| Specifications | |
|-----------------------|---|
| Supply voltage | 240V a.c. |
| Mode of operation | Maintained |
| Energy consumption | 4.1W hrc/ 3W lrc |
| Battery pack | 3 x AF NiMH stick 2.1Ah 3.6V (for 24m versions) 4 x Sub C NiMH stick 2Ah 4.8V (for 32m versions) |
| Operating temperature | 10 to 40°C |
| IP rating | IP65 |
| Body construction | Polycarbonate |
| Diffuser | Polycarbonate |
| IK rating | IK-08 |
| Compliance | IEC 62385 AS/NZS 2293 AS/NZS 60598 |

*hrc- high rate charge, lrc- low rate charge

Weatherproof LED Exit Sign **DALI Emergency**



CAT NO. 684650/D, 684651/D, 684652/D, 684670/D, 684671/D, 684672/D





- Low energy consumption save up to 70% on energy consumption*
- Two sizes: 24m and 32m viewing distance
- Long life LED light source up to 50,000 hours
- Weatherproof enclosure IP65
- High resistance polycarbonate ABS clear cover
- Includes age and oil resistant soft rubber gasket
- Removable gear tray for ease of maintenance and installation
- Two-rate charge mechanism
- High temperature Ni MH batteries
- DALI monitored
- Large terminal block for ease of connection
- Low cost maintenance
- Manufactured in Australia

| Cat. No. | Description |
|----------|-------------------------------------|
| 684650/D | WP LED Exit sml IP65 RM DALI - 24M |
| 684651/D | WP LED Exit sml IP65 RML DALI - 24M |
| 684652/D | WP LED Exit sml IP65 RMR DALI - 24M |
| 684670/D | WP LED Exit lrg IP65 RM DALI - 32M |
| 684671/D | WP LED Exit lrg IP65 RML DALI - 32M |
| 684672/D | WP LED Exit lrg IP65 RMR DALI - 32M |

RM = Running man straight

RML = Running man left


RMR = Running man right


| Accessories for 24m | | |
|---------------------|-----------------|--|
| 684690 | Wall bracket | |
| 684691 | Side bracket | |
| 684692 | Ceiling bracket | |

| Classification | |
|----------------|---------------------|
| 24m | C0- D3.2, C90- E2 |
| 32m | C0- E2.5, C90- E1.6 |

Dimensions:


24m






^{*} When compared to conventional fluorescent solutions

32m





Legrand - Australia 1300 369 777 www.legrand.com.au ABN 31 000 102 661

Legrand - New Zealand 0800 476 009 www.legrand.co.nz

Refer to your group buying office, Legrand Sales Representative or Legrand Sales Office for pricing.

Please note: specifications are subject to change without prior notice.