



### PRODUCT DETAILS



UPCOMING NEW FAST RUNNER UPDATED PHASE-OUT PRODUCTS



# ENID

## DOWNLOADS

[Datasheet](#)

### Description

<b>MOUNTING</b>	Wall mounted (WMD)
<b>LIGHT SOURCE</b>	LED
<b>OPTICAL SYSTEM</b>	Opal diffuser (OPD)
<b>LIGHT DISTRIBUTION</b>	Direct
<b>WIRING</b>	Electronic control gear FIX (ECG)
<b>MATERIALS</b>	Housing: die-cast aluminium Diffuser: polycarbonate
<b>SURFACE FINISH</b>	Housing: NHG
<b>SERVICE LIFETIME (Ta=25°C)</b>	50,000 hours / L70 / B50
<b>AMBIENT OPERATING TEMPERATURE</b>	From -10 °C to +35 °C

**AREAS OF APPLICATION** STREET AND URBAN



## Accessories

---

## List of products

PRODUCT NAME	STATUS	QUICK DOWNLOADS
ENID W1 OPAL LED 490lm/840 1x12W, FIX, -	New	<a href="#">RFA</a> / <a href="#">3DS</a> / <a href="#">IES</a> / <a href="#">LDT</a> / <a href="#">CURVE</a> /
ENID W1 OPAL LED 445lm/830 1x12W, FIX, -	New	<a href="#">RFA</a> / <a href="#">3DS</a> / <a href="#">IES</a> / <a href="#">LDT</a> / <a href="#">CURVE</a> /
ENID W2 OPAL LED 445lm/830 1x12W, FIX, -	New	<a href="#">RFA</a> / <a href="#">3DS</a> / <a href="#">IES</a> / <a href="#">LDT</a> / <a href="#">CURVE</a> /
ENID W2 OPAL LED 490lm/840 1x12W, FIX, -	New	<a href="#">RFA</a> / <a href="#">3DS</a> / <a href="#">IES</a> / <a href="#">LDT</a> / <a href="#">CURVE</a> /

The manufacturer reserves all rights to make changes in materials and components used in production of lighting fittings.