

PRODUCT FAMILY DATASHEET

LED PERFORMANCE TRI COLOUR BATTEN

LED batten luminaires with slide switch for adjusting one of selectable light colors



AREAS OF APPLICATION

- Offices
- Commercial lighting
- Storage rooms

PRODUCT BENEFITS

- Homogeneous light output
- Mercury-free technology
- Slim housing

PRODUCT FEATURES

- Uniform illumination
- Three light colors selectable via slide switch
- Color rendering index R_a : > 80
- Beam angle: 110°
- Type of protection: IP20
- Protection class: I
- Power factor: > 0.9



TECHNICAL DATA

Product description	Electrical data			Photometrical data		Dimensions & weight				Colors & materials	
	Nominal wattage	Nominal voltage	Mains frequency	Color temperature	Luminous flux	Length	Width	Height	Product weight	Body material	Product color
LDPFM BATTEN 1500 45 W 3000 K 4000 5000 Blade	45.00 W	220...240 V	50 Hz	3000/4000/5000 K	4500/4950 lm	1500 mm	75.0 mm	31.0 mm	750.00 g	Aluminum	White
LDPFM BATTEN 1200 40 W 3000 K 4000 5000 Blade	40.00 W	220...240 V	50 Hz	3000/4000/5000 K	4000/4400 lm	1200 mm	75.0 mm	31.0 mm	605.00 g	Aluminum	White
LDPFM BATTEN 600 20 W 3000 K 4000 5000 Blade	20.00 W	220...240 V	50 Hz	3000/4000/5000 K	2000/2200 lm	600.0 mm	75.0 mm	31.0 mm	320.00 g	Aluminum	White
LDPFM BATTEN 1500 50 W 3000K 4000 5700 Narrow	50.00 W	220...240 V	50/60 Hz	3000/4000/5700 K	5250 lm	1445 mm	60.0 mm	60.0 mm	2300.00 g	Polyvinyl chloride (PVC)/POL	White
LDPFM BATTEN 1200 40 W 3000 K 4000 5700 Narrow	40.00 W	220...240 V	50/60 Hz	3000/4000/5700 K	4200 lm	1165 mm	60.0 mm	60.0 mm	1900.00 g	Polyvinyl chloride (PVC)/POL	White
LDPFM BATTEN 600 20 W 3000 K 4000 5700 Narrow	20.00 W	220...240 V	50/60 Hz	3000/4000/5700 K	2100 lm	595.0 mm	60.0 mm	60.0 mm	1000.00 g	Polyvinyl chloride (PVC)/POL	White

Product description	Cover material	Temperatures & operating conditions	Capabilities		Certificates & standards	
		Ambient temperature range	Dimmable	Type of connection	Protection class	Type of protection
LDPFM BATTEN 1500 45 W 3000 K 4000 5000 Blade	Polycarbonate (PC)	-20...45 °C	No	Terminal	I	IP20
LDPFM BATTEN 1200 40 W 3000 K 4000 5000 Blade	Polycarbonate (PC)	-20...45 °C	No	Terminal	I	IP20
LDPFM BATTEN 600 20 W 3000 K 4000 5000 Blade	Polycarbonate (PC)	-20...45 °C	No	Terminal	I	IP20
LDPFM BATTEN 1500 50 W 3000K 4000 5700 Narrow		-10...40 °C	No	Terminal	I	IP20
LDPFM BATTEN 1200 40 W 3000 K 4000 5700 Narrow		-10...40 °C	No	Terminal	I	IP20
LDPFM BATTEN 600 20 W 3000 K 4000 5700 Narrow		-10...40 °C	No	Terminal	I	IP20

APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075207493	Shipping carton box 10	1530 mm x 205 mm x 185 mm	9998.00 g	58.03 dm ³
4058075207479	Shipping carton box 10	1230 mm x 205 mm x 185 mm	8137.00 g	46.65 dm ³
4058075207455	Shipping carton box 10	630 mm x 205 mm x 185 mm	4407.00 g	23.89 dm ³
4058075217928	Shipping carton box 6	1480 mm x 225 mm x 150 mm	16780.00 g	49.95 dm ³
4058075217904	Shipping carton box 6	1200 mm x 225 mm x 150 mm	13864.00 g	40.50 dm ³
4058075217881	Shipping carton box 6	630 mm x 225 mm x 150 mm	7420.00 g	21.26 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.